

Eaton XTCS250L22A

Catalog Number: XTCS250L22A

Eaton XT IEC contactor, 250A, 110 Vdc 40 Hz, 250 Vdc 60 Hz, 2NO-2NC, 250A, Frame L, 140 mm, 40-60 Hz, 75, 100, 200, 250 hp (3PH @200, 230, 460, 575 V), Three-pole , S-series, Screw terminals, FVNR

General specifications

Product Name	Catalog Number
Eaton XT IEC contactor	XTCS250L22A
EAN	Product Length/Depth
4015082741891	10 in
Product Height	Product Width
7 in	9 in
Product Weight	Compliances
16 lb	RoHS Compliant CE Marked
Certifications	Catalog Notes
UL Listed CSA Certified IEC 60947 EN 60947	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)



Product specifications

Contact configuration

2 NO, 2 NC

Coil voltage

110-250 Vdc

Series

XT IEC /S-

Type

Full voltage non-reversing contactor

HP rating - max

75, 100, 200, 250 hp (3PH @200,230,460,575 V)

Continuous ampere rating

250 A

Frequency rating

40-60 Hz

Terminals

Screw terminals

Operation

Non-reversing

Amperage Rating

250 A

Number Of Poles

Three-pole

Resources

Catalogs

[Eaton's Volume 5—Motor Control and Protection](#)

Specifications and datasheets

[Eaton Specification Sheet - XTCS250L22A](#)

[Voltage Sag Ride Through for XT IEC Contactor Frames L - N](#)

[Global Data Sheet - XTCS250L22A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)