

Eaton P60G28T1518CUB

Catalog Number: P60G28T1518CUB

Eaton Mini-Power center, 15 kVA Mini Power Center 3PH 600V to 208Y/120V Bolt-on breakers, Copper Windings 18 spaces

General specifications

Product Name	Catalog Number
Eaton Mini-Power center	P60G28T1518CUB
UPC	Product Length/Depth
786680226175	9.4 in
Product Height	Product Width
26 in	28.8 in
Product Weight	Warranty
320 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
NAFTA	UL Listed CSA Certified ANSI IEEE Certified



Physical Attributes

Coil material

Copper

Enclosure

NEMA 3R

Frame

289B

Insulation

180 °C

Mounting

Wall Mount

Tap size

2 at -5% FCBN

Type

Mini-power center

Wiring connection

M60G1H

Performance Ratings

Frequency rating

60 Hz

kVA

15 kVA

Kva Rating

15 kVA

Phase

Three-phase

Primary voltage

600 V

Secondary Voltage

208Y/120 V

Sound Level

NEMA ST-20

Temperature rise

115 °C rise

Volt ampere rating

15 kVA

Miscellaneous

Modification 1

NEMA 3R

Weathershield

Not required

Resources

Catalogs

[Eaton's Volume 2—Commercial Distribution](#)

Multimedia

[Eaton's Transformer Flex Center](#)

Specifications and datasheets

[Eaton Specification Sheet - P60G28T1518CUB](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)