Eaton DH1-35034FB-C21C

Catalog Number: DH1-35034FB-C21C

Eaton PowerXL DH1 VFD, 30HP, 22KW, keypad, DC choke, EMC filter, NO brake, Modbus RTU/TCP, BACnet MSTP/IP, 575V, 34A

General specifications

Product Name

Catalog Number

Eaton PowerXL DH1 variable frequency DH1-35034FB-C21C

drive

UPC

786689049560

Product Length/Depth

Product Height

27.3 in

16 in

Product Width

Product Weight

12.1 in

53.15 lb

Warranty

Compliances

applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all

Eaton Selling Policy 25-000 generally

GoST-R RoHS Compliant CE Marked

C-Tick Compliant

inclusive coverage parts labor and travel.

Certifications

EN ISO 13849-1 IEC 61508 UL 508C EN 62061 cUL Listed UL Listed



Product specifications

Max overload

110% for 1 minute

Communication interface

PROFIBUS-DP

Motor control modes

Frequency Control, Speed Control, Open Loop Speed Control,

Open Loop Torque Control

Internal DC choke

Yes

Conformal coated boards

Yes

Low overload (VT) kW

22 kW

Low overload (VT) hp

30 HP

Low overload (VT) amps

34A

Amperage Rating

34A

Communications onboard

BACnet/IP, Modbus TCP, Modbus RTU, BACnet MS/TP

Motor type

Induction

Output frequency range

0 - 400 Hz

Series

DH1

Electromagnetic compatibility filter

EMC

User interface

Graphical Keypad

Relay outputs

3

Power consumption

22 kW

Resources

Catalogs

Adjustable Frequency Drives

Specifications and datasheets

Eaton Specification Sheet - DH1-35034FB-C21C

Input voltage range

525 - 600 Vac

Horsepower

30 hp

Recommended fuse size

45A

Keypad

Included

Input frequency range

50 - 60 Hz

Voltage rating

575 V



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia