



Angle Grinder Paddle Switch Trigger series



Photo: GA5050

Powerful 1,300 W Motor with Paddle Switch Trigger



Photo: GA5052



**Angle of side grip to
gear housing: 110°**

100mm	115mm	125mm	
GA4050	GA4550	GA5050	
GA4050R	GA4550R	GA5050R	Soft start/ Anti-restart function
GA4051R	GA4551R	GA5051R	Undetachable wheel cover Soft start/ Anti-restart function



**Angle of side grip to
gear housing: 90°**

115mm	125mm	
GA4552	GA5052	
GA4552R	GA5052R	Soft start/ Anti-restart function
GA4553R	GA5053R	Undetachable wheel cover Soft start/ Anti-restart function



Anti-drop holders

allows to attach anti-drop strap, etc.



Easy-to-hold barrel grip

provides less hand fatigue and more control of the machine due to:

- Grip circumference smaller than 9564P series
- Ergonomic design



With soft start

GA4050R/ GA4051R/ GA4550R/ GA4552R/ GA4551R/ GA4553R/ GA5050R/ GA5052R/ GA5051R/ GA5053R

minimizes start-up shock and makes the tool start smoothly

With anti-restart function

GA4050R/ GA4051R/ GA4550R/ GA4552R/ GA4551R/ GA4553R/ GA5050R/ GA5052R/ GA5051R/ GA5053R

Minimizes accidental start-up even if the tool is plugged to power source with the switch "ON".

Undetachable wheel cover

GA4051R/ GA4551R/ GA5051R/ GA4553R/ GA5053R

designed not to be easily detached by user (for construction workers, metal workers, etc.)

	Wheel size			Angle of side grip to gear housing	Soft start	Anti-restart function	Undetachable wheel cover
	100mm	115mm	125mm				
Model No.	GA4050	GA4550	GA5050	110°	—	—	—
	GA4050R	GA4550R	GA5050R		●	●	—
	GA4051R	GA4551R	GA5051R		●	●	●
	—	GA4552	GA5052	90°	—	—	—
	—	GA4552R	GA5052R		●	●	—
	—	GA4553R	GA5053R		●	●	●

Accessories

Dust collection wheel guard

A: for offset diamond wheel
B: for diamond wheel



Part No.	Size	Type
*191F81-2	125mm	A
*191G06-2	125mm	B



*Cannot be installed undetachable wheel cover models

Cutting wheel cover attachment for cutting work

Can be attached to the wheel cover for grinding with easy assembling.

Part No.	Size
199709-0	115mm
199710-5	125mm



Wheel cover

for cut-off wheel

Part No.	Size
*162555-4	100mm
*162556-2	115mm
*162557-0	125mm



Vibration proof grip set

Part No. 194514-0



Dust cover attachment set

Part No. 199514-5



Angle Grinder Paddle Switch Trigger series

260

	GA4050	GA4550/ GA4552	GA5050/ GA5052
Double Insulation			
Soft Start (GA4050R, GA4051R, GA4550R, GA4551R, GA4552R, GA4553R, GA5050R, GA5051R, GA5052R, GA5053R)			
Dust Collection (GA4050R, GA4550R, GA5050R, GA4552R, GA5052R/R)			
Anti-restart function model	GA4050R	GA4550R/ GA4552R	GA5050R/ GA5052R
Undetachable wheel cover model	GA4051R	GA4551R/ GA4553R	GA5051R/ GA5053R
Continuous rating input	1,300W	1,300W	1,300W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
No Load Speed (RPM)	11,000	11,000	11,000
Vibration Level (Normal side grip)	Surface Grinding: 6.5 m/s ² Disc Sanding: 2.5 m/s ² or less	Surface Grinding: 7.0 m/s ² Disc Sanding: 2.5 m/s ²	Surface Grinding: 7.5 m/s ² Disc Sanding: 2.5 m/s ² or less
Sound Pressure Level	91 dB(A)	91 dB(A)	91 dB(A)
Sound Power Level	102 dB(A)	102 dB(A)	102 dB(A)
Dimensions (L x W x H)	325x117x110 mm (12-3/4"x4-5/8"x4-5/16")	325x130x117 mm (12-3/4"x5-1/8"x4-5/8")	325x140x117 mm (12-3/4"x5-1/2"x4-5/8")
Net weight	GA4050/R: 2.3-2.6 kg (5.1-5.7 lbs.) GA4051R: 2.3-2.5 kg (5.1-5.5 lbs.)	GA4550/R, GA4552/R: 2.4-2.8 kg (5.3-6.2 lbs.) GA4551R, GA4553R: 2.5-2.7 kg (5.5-6.0 lbs.)	GA5050/R, GA5052/R: 2.5-2.8 kg (5.5-6.2 lbs.) GA5051R, GA5053R: 2.5-2.7 kg (5.5-6.0 lbs.)
Power supply cord	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)	2.5 m (8.2 ft.)

Standard Equipment :

Depressed Center Wheel, Side Grip, Wheel Cover, Lock Nut Wrench

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table.
Items of standard equipment and specifications may vary by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN 202009