HAMMER-DRILL BIT SETS

HAMMER-DRILL BIT SETS

Description	Includes	Part No.
3 Pc 3-Flat SECURE GRIP™ Hammer-Drill Bit Set	(1) 5/32" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 1/4" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit	48-20-8850
5 Pc 3-Flat SECURE GRIP™ Hammer-Drill Bit Set	(1) 5/32" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 1/4" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 5/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/8" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit	48-20-8851
6 Pc 3-Flat SECURE GRIP™ Hammer-Drill Bit Set	(1) 5/32" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (2) 1/4" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 5/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/8" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit	48-20-8856
7 Pc 3-Flat SECURE GRIP™ Hammer-Drill Bit Set	(1) 1/8" x 3" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 5/32" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 1/4" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 5/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/8" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 1/2" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit	48-20-8857
7 Pc 3-Flat SECURE GRIP™ Hammer-Drill Bit Set	(1) 5/32" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (2) 3/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (2) 1/4" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 5/16" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit (1) 3/8" x 6" 3-Flat SECURE GRIP™ Hammer-Drill Bit	48-20-8852



4-CUTTER SDS PLUS DRILL BITS

OVERVIEW

MILWAUKEE® MX4™ 4-Cutter SDS Plus Rotary Hammer-Drill Bits provide up to 4X Life in Rebar and up to 20% more holes per charge in cordless rotary hammers. The enhanced rebar guards and 4-Cutter 90° head design provide increased life and durability in hard aggregate and rebar. Breaker point pulverizes the material more effectively, resulting in faster drilling speeds. The variable flute allows for maximum debris extraction leading to up 20% more holes per charge in cordless rotary hammers while making it a very durable bit in corded and cordless rotary hammers. Additionally, MX4™ features a centering tip for exact spot drilling, wear mark indicator indicating when the bit no longer meets ANSI diameter requirements, and a reinforced flute for durability and minimized vibration. A welded tip is featured from sizes 3/16" to 5/16". The increased life and efficiency of the MX4™ 4-Cutter drill bit line provides the ideal solution in general concrete and reinforced concrete for cordless and corded rotary hammer users.

FEATURES

- 4-Cutter 4x90° Tip Geometry to avoid lock up in rebar
- Enhanced Rebar Guards for increased durability
- Variable Flutes for maximum debris extraction







4-CUTTER SDS PLUS DRILL BITS

	000 1 200				
Diameter	Usable Length	Length	1 Pack	10 Pack	15 Pack
5/32"	4"	6"	48-20-7308		
3/16"	2"	4"	48-20-7310	-	-
3/16"	4"	6"	48-20-7311	-	48-20-7911
3/16"	6"	8"	48-20-7312	-	-
3/16"	8"	10"	48-20-7313	-	-
3/16"	10"	12"	48-20-7314	-	-
1/4"	2"	4"	48-20-7330	-	-
1/4"	4"	6"	48-20-7331	-	48-20-7931
1/4"	6"	8"	48-20-7332	-	-
1/4"	8"	10"	48-20-7334	-	-
1/4"	10"	12"	48-20-7335	-	-
5/16"	4"	6"	48-20-7341	-	-
5/16"	10"	12"	48-20-7344	-	-
3/8"	4"	6"	48-20-7351	48-20-7951	-
3/8"	10"	12"	48-20-7354	-	-
3/8"	16"	18"	48-20-7357	-	-
7/16"	4"	6"	48-20-7361	-	-
7/16"	10"	12"	48-20-7364	-	-
1/2"	4"	6"	48-20-7371	48-20-7971	-
1/2"	10"	12"	48-20-7374	-	-
1/2"	16"	18"	48-20-7377	-	-

4-CUTTER SDS PLUS DRILL BITS

Diameter	Usable Length	Length	1 Pack	10 Pack	15 Pack
9/16"	4"	6"	48-20-7381	-	-
9/16"	10"	12"	48-20-7384	-	-
9/16"	16"	18"	48-20-7387	-	-
5/8"	6"	8"	48-20-7200	-	-
5/8"	10"	12"	48-20-7203	-	-
5/8"	16"	18"	48-20-7206	-	-
3/4"	6"	8"	48-20-7210	-	-
3/4"	8"	10"	48-20-7212	-	-
3/4"	10"	12"	48-20-7215	-	-
3/4"	16"	18"	48-20-7220	-	-
7/8"	6"	8"	48-20-7225	-	-
7/8"	8"	10"	48-20-7228	-	-
7/8"	10"	12"	48-20-7230	-	-
7/8"	16"	18"	48-20-7236	-	-
1"	8"	10"	48-20-7240	-	-
1"	16"	18"	48-20-7246	-	-
1-1/8"	8"	10"	48-20-7250	-	-
1-1/8"	16"	18"	48-20-7256	-	-
1-1/4"	16"	18"	48-20-7266	-	-



This product complies with ANSI B212.15 standard



SPLINE ONE-PIECE CORE BITS

OVERVIEW

MILWAUKEE's One-Piece Carbide Tipped Core Bits are ideal for drilling large holes where the depth is relatively shallow. The core bit cuts a kerf only. The inside core must be removed by the operator before deeper drilling can be accomplished. Centering Bit 48-20-5495 is included. Use Drift Key 48-20-5497 (not included) to remove centering bit from the one-piece core bit. The one-piece core bits are available in SDS Max or Spline shanks. They come in a variety of diameters ranging from 1-1/2" to 6" with overall lengths of 11-3/8" or 22" and a drilling depth of 3". The asymmetric tooth pitch with alternating tooth geometries creates faster material pulverization. The one-piece design maximizes energy transfer and the thick wall core body is durable even in large hammers. The fluted core exterior minimizes friction loss and removes debris faster.



Visit Our Digital Catalog at

www.milwaukeetool.com/pta

FEATURES

- Asymmetrical and Alternating Teeth for faster material pulverization
- Thick Wall Core Body for durability even in large hammers
- Includes Centering Bit to reduce bit walking and create exact spot drilling

SPLINE ONE-PIECE CORE BITS

Diameter	Length	Part No.
1-1/2"	11-3/8"	48-20-5450
1-1/2"	22"	48-20-5452
1-3/4"	11-3/8"	48-20-5454
1-3/4"	22"	48-20-5456
2"	11-3/8"	48-20-5458
2"	22"	48-20-5460

Diameter	Length	Part No.
2-5/8"	11-3/8"	48-20-5462
2-5/8"	22"	48-20-5464
3-1/8"	11-3/8"	48-20-5470
3-1/8"	22"	48-20-5472
3-9/16"	11-3/8"	48-20-5478
3-9/16"	22"	48-20-5480

Diameter	Length	Part No.
4"	11-3/8"	48-20-5482
4"	22"	48-20-5484
5"	11-3/8"	48-20-5486
5"	22"	48-20-5488
6"	22"	48-20-5490

SPLINE ONE-PIECE CORE BITS ACCESSORIES

Description	Part No.
Centering Bit for One-Piece Core Bits	48-20-5495
Drift Key for One-Piece Core Bits	48-20-5497

SPLINE OR ROUND/HEX DEMOLITION STEEL



SPLINE OR ROUND/HEX DEMOLITION STEEL

Style	Size	1 Pack	15 Pack (Bulk)	25 Pack (Bulk)
Bull Point	12"	48-62-2000	-	48-62-2100

SPLINE OR ROUND/HEX DEMOLITION STEEL

STERE OF HOURD/HEADERIOR STEEL				
Style	Size	1 Pack	15 Pack (Bulk)	25 Pack (Bulk)
Bull Point	18"	48-62-2010	-	48-62-2110
Bushing Tool	1-3/4" x 9-1/2"	48-62-2070	48-62-2170	-
Clay Spade	4-1/2" x 16-3/4"	48-62-2095	-	-
Flat Chisel	1" x 12"	48-62-2020	-	48-62-2120
Flat Chisel	1" x 18"	48-62-2030	-	48-62-2130
Ground Rod Driver	10"L - 5/8" & 3/4" Rod Dia.	48-62-2046	-	-
Scaling Chisel	1-1/2" x 12"	48-62-2040	-	-
Scaling Chisel	2" x 12"	48-62-2050	-	48-62-2150
Scaling Chisel	3" x 12"	48-62-2055	-	48-62-2155
Scaling Chisel	4-1/2" x 14"	48-62-2057	-	-
Scraping Chisel	2" x 12"	48-62-2065	-	-
Seam Tool	1" x 12"	48-62-2080	-	-
Slotting Chisel	1-1/4" x 12"	48-62-2060	-	-
Tamper Plate	5" x 5"	48-62-3060	-	-
Tamper Shank	12"	48-62-2097	-	-

3/4" HEX DEMOLITION STEEL



3/4" HEX DEMOLITION STEEL

Style	Size	Part No.
Asphalt Cutter	5" x 16-1/2"	48-62-3090
Bull Point	12"	48-62-3000
Bull Point	18"	48-62-3005
Bushing Tool	1-3/4" x 9-1/2"	48-62-3085
Clay Spade	4-1/2" x 16-3/4"	48-62-3040
Flat Chisel	1" x 12"	48-62-3010
Flat Chisel	1" x 18"	48-62-3015
Ground Rod Driver	9-3/4"L - 5-8" & 3/4" Rod Dia.	48-62-3070
Scaling Chisel	1-1/2" x 12"	48-62-3020
Scaling Chisel	2" x 12"	48-62-3035
Scaling Chisel	3" x 12"	48-62-3030
Scraping Chisel	2" x 12"	48-62-3025
Tamper Shank	12"	48-62-3065



1-1/8" HEX DEMOLITION STEEL



1-1/8" HEX DEMOLITION STEEL

Style	Size	Part No.
Asphalt Cutter	5" x 17-1/2"	48-62-4020
Clay Spade	5-1/2" x 20"	48-62-4030
Ground Rod Driver	15-1/2"L x 3"	48-62-4045
Moil Point	20"	48-62-4000
Narrow Chisel	20-1/2"	48-62-4005
Scaling Chisel	3" x 20-1/2"	48-62-4010
Spike & Pin Driver	14-1/2"	48-62-4040
Tamper Plate	6" x 6"	48-62-4050
Tamper Plate	8" x 8"	48-62-4055
Tamper Shank	6" x 6"	48-62-4060
Tent Stake Driver - Head Only	5-1/2"L/ 3-1/2"OD/ 2-3/4"ID	48-62-4061

MAX-LOK™ EXTENSIONS AND ADAPTERS



MAX-LOK*

Description	Part No.
MAX-LOK™ Connection, includes Grease	48-20-6950
MAX-LOK [™] Replacement Grease	49-08-5385

EXTENSIONS

Shank	Length	Part No.
SDS Plus	12-1/2"	48-20-6980
SDS Plus	29-1/2"	48-20-6982
SDS Max	12-1/2"	48-20-6960
SDS Max	29-1/2"	48-20-6962
SDS Max	43"	48-20-6964
SDS Max	63"	48-20-6966
SDS Max	82-1/2"	48-20-6968
Spline	12-1/2"	48-20-6970
Spline	29-1/2"	48-20-6972
Spline	43"	48-20-6974

PLUS-LOK™ SDS PLUS EXTENSIONS

OVERVIEW

MILWAUKEE® PLUS-LOK™ SDS Plus Extensions provide increased access in tough to reach areas and around obstructions. The extensions are universal, fitting all brands of SDS Plus rotary hammers and accessories including but not limited to drill bits, chisels, core bits, and anchor installation solutions. Due to their small profile design, the PLUS-LOK™ Extensions are ideal for drilling deep through holes with drill bits 7/8" and larger. Additionally, the auto-insert mechanism allows for tool-free connection and ease of use. By increasing accessibility and decreasing the number of drill bits needed to complete a job, the universal PLUS-LOK™ SDS Plus Extensions allow users to reach more and maximize productivity.

FEATURES

- 12" and 18" Length for increased accessibility in tough to reach applications
- Ideal for tight access in and around obstructions
- Universal extension fits all SDS Plus rotary hammers
- Compatible with all SDS Plus accessories including drill bits, chisels, core bits, and anchor installation solutions

PLUS-LOK[™] SDS PLUS EXTENSIONS

Shank	Length	Part No.
PLUS-LOK™ SDS Plus Extension	12"	48-20-6940
PLUS-LOK™ SDS Plus Extension	18"	48-20-6945

ADAPTERS

CARBIDE BIT ADAPTERS

Tool Shank	Bit Shank	Part No.
SDS Plus Dust Shield	-	48-03-3030
SDS Max	SDS Plus	48-03-3025
SDS Max	Spline	48-03-3012
SDS Plus	1/2" Chuck	48-03-3005
Spline	A-Taper	48-66-6502
Spline	B-Taper	48-66-6503
Spline	SDS Max	48-03-3010
Spline	SDS Plus	48-03-3015

