



# LED General Purpose

Combining a comfortable, pleasing atmosphere with energy efficiency is now possible with STANDARD's smooth dimming LED lamps. Choose from our large selection of lamp shapes and create your own style while saving on energy and maintenance costs.

From Omni lamps to small halogen replacements, these lamps deliver a brighter look and provide the same even, crisp and comfortable lighting as traditional lamps. A wide selection of color temperatures is offered to obtain the desired lighting effect and can be adapted to all applications.



A19

A19 4 pack

A19 GU24

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>A19 40 W equivalent</b>												
67948	LED/A19/S5/6W/27K/STD	6	E26	120	2 700	Frost	80	25 000	480	40	Yes	1/100
67949	LED/A19/S5/6W/30K/STD	6	E26	120	3 000	Frost	80	25 000	480	40	Yes	1/100
67950	LED/A19/S5/6W/40K/STD	6	E26	120	4 000	Frost	80	25 000	480	40	Yes	1/100
67951	LED/A19/S5/6W/50K/STD	6	E26	120	5 000	Frost	80	25 000	480	40	Yes	1/100
<b>60 W equivalent</b>												
67952	LED/A19/S5/9W/27K/STD	9	E26	120	2 700	Frost	80	25 000	800	60	Yes	1/100
67953	LED/A19/S5/9W/30K/STD	9	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/100
67954	LED/A19/S5/9W/40K/STD	9	E26	120	4 000	Frost	80	25 000	800	60	Yes	1/100
67955	LED/A19/S5/9W/50K/STD	9	E26	120	5 000	Frost	80	25 000	800	60	Yes	1/100
<b>60 W equivalent - 4 pack</b>												
68001	LED/A19/S2/9W/27K/STD 4P	9	E26	120	2 700	Frost	80	25 000	800	60	Yes	1/96
68002	LED/A19/S2/9W/30K/STD 4P	9	E26	120	3 000	Frost	80	25 000	800	60	Yes	1/96
68003	LED/A19/S2/9W/40K/STD 4P	9	E26	120	4 000	Frost	80	25 000	800	60	Yes	1/96
68004	LED/A19/S2/9W/50K/STD 4P	9	E26	120	5 000	Frost	80	25 000	800	60	Yes	1/96
<b>60 W equivalent - GU24</b>												
66275	A19/9.8W/27K/GU24/PRO/STD	9.8	GU24	120	2 700	Frost	83	25 000	814	60	Yes	6/48
66276	A19/9.8W/30K/GU24/PRO/STD	9.8	GU24	120	3 000	Frost	82	25 000	887	60	Yes	6/48
66277	A19/9.8W/40K/GU24/PRO/STD	9.8	GU24	120	4 000	Frost	86	25 000	868	60	Yes	6/48
<b>75 W equivalent</b>												
66184	LED/A19/S4/11W/27K/STD	11	E26	120	2 700	Frost	81	25 000	1 109	75	Yes	6/48
67957	LED/A19/S5/12W/30K/STD	12	E26	120	3 000	Frost	80	25 000	1 100	75	Yes	1/100
67958	LED/A19/S5/12W/40K/STD	12	E26	120	4 000	Frost	80	25 000	1 100	75	Yes	1/100
67959	LED/A19/S5/12W/50K/STD	12	E26	120	5 000	Frost	80	25 000	1 100	75	Yes	1/100
<b>100 W equivalent</b>												
66188	LED/A19/S4/15W/27K/STD	15	E26	120	2 700	Frost	82	25 000	1 629	100	Yes	6/48
66189	LED/A19/S4/15W/30K/STD	15	E26	120	3 000	Frost	81	25 000	1 630	100	Yes	6/48
66190	LED/A19/S4/15W/40K/STD	15	E26	120	4 000	Frost	85	25 000	1 692	100	Yes	6/48
66191	LED/A19/S4/15W/50K/STD	15	E26	120	5 000	Frost	85	25 000	1 725	100	Yes	6/48

Lumen values are derived from photometric testing  
For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)





A21



A19 15 W & Trilight

Order code	Description	Watts (W)	Base	Volts (VAC)	Color temp. (K)	Finish	CRI	Life L70 (hrs)	Lumen output (lm)	Traditional equivalent (W)	Dimming capability (Yes/No)	Case qty (inner/master)
<b>A21</b>												
<b>100 W equivalent</b>												
67960	LED/A21/S5/15W/27K/STD	15	E26	120	2 700	Frost	80	25 000	1 600	100	Yes	1/100
67961	LED/A21/S5/15W/30K/STD	15	E26	120	3 000	Frost	80	25 000	1 600	100	Yes	1/100
67962	LED/A21/S5/15W/40K/STD	15	E26	120	4 000	Frost	80	25 000	1 600	100	Yes	1/100
67963	LED/A21/S5/15W/50K/STD	15	E26	120	5 000	Frost	80	25 000	1 600	100	Yes	1/100
<b>Trilight</b>												
65613	LED/A19/S2/12W/27K/3WAY/STD	3	E26	120	2 700	Frost	81	25 000	280	30	No	6/24
		9							950	70		
		12							1 200	100		
65614	LED/A19/S2/12W/30K/3WAY/STD	3	E26	120	3 000	Frost	83	25 000	280	30	No	6/24
		9							950	70		
		12							1 200	100		

Lumen values are derived from photometric testing  
 For a complete list of compatible dimmers and ENERGY STAR qualified products, please visit [www.standardpro.com](http://www.standardpro.com)

