# Eaton LS-11

# Catalog Number: LS-11

Eaton LS-Titan Miniature DIN Limit Switch, Top Push Plunger, Polyamide PA66-GF25 enclosure, 6A max AC, 3A max DC, 1NO-1NC, Slow Make Before Break, Positive Opening, 6A at 240Vac, 3A at 24Vdc, Cage Clamp, ±0.02mm accuracy

### General specifications

Product Name Catalog Number Eaton LS-Titan miniature DIN limit switch LS-11

UPC	Product Length/Depth
786685514178	1.22 in
Product Height	Product Width
2.99 in	1.32 in
Product Weight	Warranty
.1188 lb	1 year
Compliances	Certifications
RoHS Compliant	UL Listed



## Product specifications

#### Enclosure material

Polyamide PA66-GF25

Contact configuration

1 NO-1 NC, slow make before break, positive opening

#### Туре

LS-Titan

Accuracy

±0.02mm

Switch type Top push plunger

Contact Rating 6A at 240Vac, 3A at 24Vdc

Operating temperature - min

-13 °F

Maximum AC current

6 A

Maximum DC current

3 A

Operating temperature - max

158 °F

Connection

Cage clamps

Environmental rating

IP66, IP67





Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.com All other trademarks are © 2023 Eaton. All Rights property of their respective Reserved. owners.



Eaton.com/socialmedia

#### Resources

Specifications and datasheets

Eaton Specification Sheet - LS-11