

## SKINDICHT® MA-M/NPT

SKINDICHT® MA-M/NPT, metric cable gland accessories as adapter from a metric outer thread to an NPT inner thread





Assembly time



Space requirement

### **Benefits**

Allows an easy transition from a metric male thread to an NPT female thread.

Withstands temperatures up to +200 °C.

Available for thread sizes up to NPT1" or up to M40.

Article numbers ending in "LF" are lead-free product alternatives with the same product properties. "Lead-free" articles do not contain lead, which is currently still allowed to make up to four percent in copper alloys. It could be banned in the future according to the RoHS Directive.

### **Application range**

Adapter from a metric outer thread to an NPT inner thread.

For applications with different types of threads.

Withstands high chemical and mechanical stress.

Suitable for outdoor use.

### **Product Make-up**

Metric connection thread acc. to DIN EN 60423 Basis for technical information DIN IEC 62444

### **Technical Data**

Classification ETIM 5: ETIM 5.0 Class-ID: EC000441

ETIM 5.0 Class-Description: Cable screw gland

Classification ETIM 6: ETIM 6.0 Class-ID: EC000441

ETIM 6.0 Class-Description: Cable screw gland

On request: with O-ring fitted

Material: Nickel-plated brass

Temperature range: -60 °C to +200 °C

Last Update (25.05.2023)

©2023 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02\_03.16



# **SKINDICHT® MA-M/NPT**

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products. Prices are net prices without VAT and surcharges. Sale to business customers only.

# **SKINDICHT® MA-M/NPT**

Article number	Thread, male M1	Thread, female NPT	Pieces / PU	
SKINDICHT® MA-M / NPT	·	·	·	
54020100	16 x 1.5	1/2"	50	
54020110	20 x 1.5	1/2"	50	
54020120	25 x 1.5	1/2"	25	
54020130	25 x 1.5	3/4"	25	
54020140	32 x 1.5	1/2"	25	
54020152	32 x 1.5	1"	25	
54020153	40 x 1.5	1 1/4"	10	
54020100LF	16 x 1.5	1/2"	50	
54020110LF	20 x 1.5	1/2"	50	
54020120LF	25 x 1.5	1/2"	25	
54020130LF	25 x 1.5	3/4"	25	