


FLKM-D15 SUB/S - Interface module



2281131

<https://www.phoenixcontact.com/in/products/2281131>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



VARIOFACE module, with screw connection and D-Subminiature pin strip, for mounting on NS 35/7.5 or NS 32, 15-pos.

Commercial Data

Item number	2281131
Packing unit	10 pc
Minimum order quantity	1 pc
Sales Key	CK2
Product Key	CK2222
Catalog Page	Page 248 (IF-2007)
GTIN	4017918054588
Weight per Piece (including packing)	90.45 g
Weight per Piece (excluding packing)	83.374 g
Customs tariff number	85369010
Country of origin	DE

FLKM-D15 SUB/S - Interface module



2281131

<https://www.phoenixcontact.com/in/products/2281131>

Technical Data

Notes

General	For proper use, the specifications of the installation directive (see Downloads) must be observed.
---------	--

Product properties

Product type	Interface module
Product family	VARIOFACE
Number of positions	15

Insulation characteristics

Insulation	Functional insulation
------------	-----------------------

Insulation characteristics

Insulation	Functional insulation
Overvoltage category	II
Pollution degree	2

Electrical properties

Nominal voltage U_N	25 V AC
	60 V DC
Max. current carrying capacity per branch	2.5 A
	1.5 A (with even load on all branches)
Rated insulation voltage	125 V
Rated surge voltage	1.2 kV

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	D-SUB pin strip
Number of positions	15

Signaling

Status display present	No
------------------------	----

Dimensions

FLKM-D15 SUB/S - Interface module



2281131

<https://www.phoenixcontact.com/in/products/2281131>

Width	45 mm
Height	77 mm
Depth	57.5 mm

Material specifications

Housing insulation material	Polyamide 6 green
-----------------------------	-------------------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

Approvals

UKCA

Certificate	UKCA-compliant
-------------	----------------

Standards and regulations

Standards/regulations	IEC 60664
	DIN EN 50178

Mounting

Mounting type	DIN rail mounting
Mounting position	any

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

info@phoenixcontact.co.in