**PHILIPS** Lighting



# Core & Coil (71A) MH ~GT~ 450W

## CORE & COIL HID MH BAL 1000W M47 120/277/347V KIT

The basic ballast is the open core and coil which is most often used as a component within a lighting luminaire. The core and coil also forms the nucleus of Philips Advance's five other ballast configurations.

#### **Product data**

General Information						
ANSI Code	M47 1000W MH					
Lamp Type						
Number of Lamps	1 piece/unit CWA Magnetic HID					
Circuit Type						
Ballast Type						
Base Model	71A65A2					
Core Size	4 1/4 x 6 (2 Coil)					
Suitable For Outdoor Use	Yes NA					
Ignitor Catalog Number						
Ignitor Temperature Rating	NA 24 MFD					
Capacitor Value						
Capacitor Catalog Number	MD2409000					
Capacitor Requirements	480V					
Capacitor Temperature Rating	90°C					
Capacitor Diameter/Oval Dimensions	1.75 in					
Capacitor Height	3.9 in					
Automatic Restart	No					


Operating and Electrical	
Input Voltage	120/277/347 V
Input Frequency	60 Hz
Input Current (Open Circuit)	4.5/2.2/1.7 A
Input Current (Starting)	7.8/3.2/2.5 A
Input Current (Short Circuit)	4.8-7.3/2-3.1/1.6-2.6 V
Secondary Short Circuit Current	5.2-6.4 A
Constant Wattage Deviation	10%
Ballast Factor (Nom)	1
Power Factor (Nom)	0.90
Open Circuit Voltage	430 V
Input Current (Nom)	9/3.9/3.2 A A
Input Power (Nom)	1080 W
Rated Lamp Power	1000 W
Wiring	
Wire Striplength	0.5 mm
Wire Length by Color	12"
Wire Type	Stranded
Remote Wiring Configuration Allowed	Yes

### Core & Coil (71A) MH ~GT~ 450W

Max Ballast-Lamp Distance Remote Wiring Determined by AWG used					
Recommended Fuse Value	20/10/8 A				
Approval and Application					
Open Circuit Voltage Test (Volts)	385-475 V				
Approval Marks	ULR CSA certificate RoHS Compliant				
Temperature Marking	D/C/C				
UL Recognized	Yes				
Hipot Test (1 Minute)	2000 V				
Hipot Test (2 Seconds)	2500 V				
UL Insulation Class	H(180°C)				
UL Temperature Code	1029D				

CORE & COIL HID MH BAL 1000W M47				
120/277/347V KIT				
781087021958				
913700525709				
1				
1				
913700525709				
10.156 kg				

#### Dimensional drawing



MH BAL 1000W M47 120/277/347V KIT

Product	C1	C2	A1	A2	A3	B1	B2
CORE & COIL HID MH BAL 1000W	4.5 in	2.8 in	6 in	5.4 in	4.4 in	4.3 in	3.9 in
M47 120/277/347V KIT							



© 2019 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. All trademarks are owned by Signify Holding or their respective owners.

www.lighting.philips.com 2019, March 22 - data subject to change