




CONDUIT FITTINGS Non-Metallic Cable Glands



- Flame Retardant UL 94V2
- Suitable for NEMA type 4X and type 6 IP 68 5 Bar
- UL Listed, CSA Listed for certain ranges of cable
- Strain Relief
- Non-Metallic construction provides corrosion, chemical & impact protection
- Working Temperatures: -20°C (-4°F) to 100°C (+212°F)
Continuous, -30°C (-86°F) +150°C (+276°F)
Intermittent
- Sturdy Nylon 6 for Strong, lightweight construction
- Low profile cable gland for tight spots
- VDE Rated

CAT. NO.	THREAD SIZE	CLAMPING RANGE		LENGTH OF THREAD	LOCKNUT CAT. NO.
		MAX.	MIN.		
CC-NPT-38-G	3/8" NPT	0.394" / 10mm	0.197" / 5mm	0.590" / 15mm	—
CC-NPT-12-G	1/2" NPT	0.551" / 14mm	0.394" / 10mm	0.590" / 15mm	LN-501
CC-NPT-34-G	3/4" NPT	0.709" / 18mm	0.511" / 13mm	0.590" / 15mm	LN-502
CC-NPT-1-G	1" NPT	0.984" / 25mm	0.709" / 18mm	0.709" / 18mm	LN-503

CC-NPT-12-G-2	0.5" NPT	Qty. (2) 0.222" Cables 5.5mm		0.590" / 15mm	LN-501
CC-NPT-12-G-3	0.5" NPT	Qty. (3) 0.220" Cables 5.5mm		0.590" / 15mm	LN-501
CC-NPT-34-G-2	0.75" NPT	Qty. (2) 0.260" Cables 6.6mm		0.590" / 15mm	LN-502
CC-NPT-34-G-3	0.75" NPT	Qty. (3) 0.260" Cables 6.6mm		0.590" / 15mm	LN-502
CC-NPT-34-G-4	0.75" NPT	Qty. (4) 0.260" Cables 6.6mm		0.590" / 15mm	LN-502

CC-PG7-G	7 PG	0.256" / 6.5mm	0.118" / 3mm	0.315" / 8mm	LN-PG7-G
CC-PG9-G	9 PG	0.135" / 8mm	0.157" / 4mm	0.315" / 8mm	LN-PG9-G
CC-PG11-G	11 PG	0.394" / 10mm	0.197" / 5mm	0.315" / 8mm	LN-PG11-G
CC-PG135-G	13.5 PG	0.473" / 12mm	0.236" / 6mm	0.394" / 10mm	LN-PG135-G
CC-PG16-G	16 PG	0.551" / 14mm	0.394" / 10mm	0.394" / 10mm	LN-PG16-G
CC-PG21-G	21 PG	0.709" / 18mm	0.512" / 13mm	0.433" / 11mm	LN-PG21-G
CC-PG29-G	29 PG	0.984" / 25mm	0.709" / 18mm	0.433" / 11mm	LN-PG29-G
CC-PG36-G	36 PG	1.260" / 32mm	0.867" / 22mm	0.519" / 13mm	LN-PG36-G

CC-ISO-16-G	16mm ISO	0.394" / 10mm	0.197" / 5mm	0.394" / 10mm	LN-ISO-16-G
CC-ISO-20-G	20mm ISO	0.473" / 12mm	0.236" / 6mm	0.394" / 10mm	LN-ISO-20-G
CC-ISO-25-G	25mm ISO	0.709" / 18mm	0.512" / 13mm	0.394" / 10mm	LN-ISO-25-G
CC-ISO-32-G	32mm ISO	0.984" / 25mm	0.709" / 18mm	0.590" / 15mm	LN-ISO-32-G

NOTE: Suffix "G" may change indicating color.

WARRANTY: Thomas & Betts sells this product with the understanding that the user will perform all necessary tests to determine the suitability of this product for the user's intended application. Thomas & Betts warrants that this product will be free from defects in materials or workmanship for a period of two (2) years following the date of purchase. Upon prompt notification of any warranted defect, Thomas & Betts will, at its option, repair or replace the defective product. Misuse, misapplication or modification of Thomas & Betts Products immediately voids all warranties.

Limitations and Exclusions: THE ABOVE WARRANTY IS THE SOLE WARRANTY CONCERNING THIS PRODUCT, AND IS IN LIEU OF ALL OTHER WARRANTIES EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE SPECIFICALLY DISCLAIMED. LIABILITY FOR BREACH OF THE ABOVE WARRANTY IS LIMITED TO COST OF REPAIR OR REPLACEMENT OF THE PRODUCT, AND UNDER NO CIRCUMSTANCES WILL THOMAS & BETTS BE LIABLE FOR ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Thomas & Betts

A Member of the ABB Group

Thomas & Betts Corporation
Memphis, Tennessee
www.tnb.com