

# CES-B24-HFFS-PLBK - Sealing frame



0801661

<https://www.phoenixcontact.com/in/products/0801661>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Sealing frame, With locking latch, design: B24, Number of cable seals (small): 10, material: PA (halogen-free), color: black, length: 147 mm, width: 58 mm, height: 20 mm

## Your advantages

- Can also be used for standard panel cutouts for heavy-duty industrial connectors

## Commercial Data

Item number	0801661
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BF7
Product Key	BF7CAX
Catalog Page	Page 676 (C-2-2019)
GTIN	4046356674119
Weight per Piece (including packing)	181.3 g
Weight per Piece (excluding packing)	171 g
Customs tariff number	39269097
Country of origin	PL

# CES-B24-HFFS-PLBK - Sealing frame

0801661

<https://www.phoenixcontact.com/in/products/0801661>

## Technical Data


### Notes

General	Mounting screws not supplied as standard. The maximum width of the panel cutout must not exceed 51 mm (instead of 35 mm for heavy-duty industrial connectors).
---------	--

### Product properties

Type	B24
Product type	Frame for cable sleeves
Locking type	With locking latch
Frame type	Sealing frame

### Dimensions

Dimensional drawing	
Width	58 mm
Height	20 mm
Length	147 mm
Drill hole distance, horizontal	32 mm
Drill hole distance, vertical	130 mm
Hole diameter	5.5 mm

### Installation dimensions

Width of the assembly cutout	35 mm
Length of the assembly cutout	113 mm

### Material specifications

Color	black
Flammability rating according to UL 94	V0
Material (GRP)	PA (halogen-free)

### Characteristics

Number of cable seals	2 ... 10 (small seals, depending on the number of large seals installed) 0 ... 2 (large seals, depending on the number of small seals installed)
-----------------------	---

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C ... 120 °C (static)

# CES-B24-HFFS-PLBK - Sealing frame



0801661

<https://www.phoenixcontact.com/in/products/0801661>

## Mounting

Assembly instructions

One large sleeve requires the space of 4 small sleeves, M4 mounting screws (ISO 4762/DIN 912), torque for mounting screw: 1.8 Nm

A video tutorial on how to assemble the product can be found in the Downloads area, in the Video category.

Phoenix Contact 2023 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.

A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420

[info@phoenixcontact.co.in](mailto:info@phoenixcontact.co.in)