

TMT (EX6,5)R - Marker for terminal blocks



0803064

<https://www.phoenixcontact.com/in/products/0803064>

Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK E.300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snapped, snap into flat marker groove, lettering field size: 6.5 x 50000 mm, Number of individual labels: 1

Your advantages

- The TMT labeling range includes markers for all products with tall and flat marker grooves
- Quick and inexpensive marking with THERMOMARK ... roll printers from Phoenix Contact
- When combined with the right ink ribbon, the marking is highly resistant to solvents and mechanical influences
- The thermal transfer printer cutting units make it possible to trim precisely to the required length
- Labeling service: Phoenix Contact can custom-label all TMT ... markers in accordance with your requirements

Commercial Data

Item number	0803064
Packing unit	1 pc
Minimum order quantity	1 pc
Sales Key	BG2
Product Key	BG2111
Catalog Page	Page 142 (C-3-2019)
GTIN	4046356935531
Weight per Piece (including packing)	323 g
Weight per Piece (excluding packing)	323 g
Customs tariff number	39269097
Country of origin	FR

TMT (EX6,5)R - Marker for terminal blocks



0803064

<https://www.phoenixcontact.com/in/products/0803064>

Technical Data

Product properties

Product type	Terminal marking
Type	flat
Area of application	KASUGA: Marker strips for connection terminal blocks

Marking

Number of individual labels	1
Number of individual labels per row	1

Marking technology

Device	1085260 THERMOMARK ROLL 2.0
	0804501 THERMOMARK ROLLMASTER 300
	0804663 THERMOMARK ROLLMASTER 600
	1285306 THERMOMARK E.300
	1285310 THERMOMARK E.600
Ink ribbon	5148007 THERMOMARK-RIBBON 110-WMTB HF
Printability	Thermal transfer

Dimensions

Width	6.5 mm
Length	50 m
Material strength	0.50 mm

Material specifications

RoHS compliant	yes
Color	white
Material	PVC
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

Scratch test for the determining scratch resistance

Specification	DIN EN ISO 1518-1:2019-10 (following)
Requirements	≥ 5 N
Result	Test passed

Tesafilm test

Specification	DIN EN ISO 2409:2013 (following)
Result	Test passed

UV resistance

TMT (EX6,5)R - Marker for terminal blocks



0803064

<https://www.phoenixcontact.com/in/products/0803064>

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Temperature resistance

Specification	ANSI/UL 969-2018:03 (following)
Test duration	240 h
Rating 100 °C (121 °C)	Test passed

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-01):2020-03 DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Specification	ISO 175:2010 (following)
Test duration	168 h

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed
Test duration	96 h

Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
Recommended storage conditions	10 ... 30 °C / 40 ... 70 % relative humidity. Storage in the original packaging is recommended prior to processing.
Recommended ambient temperature (storage/transport)	10 °C ... 30 °C
Recommended humidity (storage/transport)	40 % ... 70 %

Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Mounting

Mounting type	snapped
---------------	---------

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT (I) Pvt. Ltd.
A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420
info@phoenixcontact.co.in