## FBS 50-6 BU - Plug-in bridge



https://www.phoenixcontact.com/in/products/3032211



Please be informed that the data shown in this PDF document is generated from our Online Catalog. Please find the complete data in the user documentation. Our General Terms of Use for Downloads are valid.



Plug-in bridge, pitch: 6.2 mm, number of positions: 50, color: blue

## Your advantages

• The 2- to 50-pos. jumpers can bridge up to 50 terminal blocks in the two bridge shafts of the CLIPLINE complete system in one step

## **Commercial Data**

Item number	3032211
Packing unit	10 pc
Minimum order quantity	10 pc
Sales Key	BE2
Product Key	BE2Z2X
Catalog Page	Page 403 (C-1-2019)
GTIN	4046356052573
Weight per Piece (including packing)	49.582 g
Weight per Piece (excluding packing)	47.436 g
Customs tariff number	85366990
Country of origin	DE

# FBS 50-6 BU - Plug-in bridge



https://www.phoenixcontact.com/in/products/3032211



## **Technical Data**

## Product properties

Product type	Jumper
Number of positions	50
Pitch	6.2 mm

## Electrical properties

Maximum load current	32 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal blocks.)

### Connection data

Maximum load current	32 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

#### **Dimensions**

Width	308.3 mm
Height	23 mm
Pitch	6.2 mm

## Material specifications

Color	blue
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-60 °C 105 °C
Ambient temperature (storage/transport)	-25 $^{\circ}\text{C}$ 60 $^{\circ}\text{C}$ (for a short time, not exceeding 24 h, -60 $^{\circ}\text{C}$ to +70 $^{\circ}\text{C})$
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C
Permissible humidity (storage/transport)	30 % 70 %

## Mounting

Mounting type	Plua-in mounting
Mounting type	Flug-in mounting

# FBS 50-6 BU - Plug-in bridge

3032211

https://www.phoenixcontact.com/in/products/3032211



Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in