



White Color:

UPC Code: 078477472552 Country Of Origin: China

#### **Available Colors:**





Light Almond

# **DHS05-1LW**

Decora In-Wall Humidity Sensor and Fan Control Switch, 1/4 HP, Residential Grade, Single Pole

Decora Humidity Sensor and Fan Control, single pole, 1/4 HP Motor, 300W LED/CFL, 600W Incandescent/Halogen, 400VA Magnetic Low Voltage, 400VA Electronic Low Voltage. Can be installed with or without a neutral wire, line and load wires are interchangeable, wallplate sold separately. Can be used to comply with the requirements of 2019 and 2022 California Title 24, Part 6, Indoor Air Quality and Mechanical Ventilation, 2019 and 2022 CALGREEN, Part II, Indoor Air Quality and Exhaust and meets requirements of ASHRAE 62.2 - White

- CONVENIENT automatically turns bath or ventilation fan on/off
- EASY TO INSTALL slim profile fits in most wallboxes
- FLEXIBLE can be installed with or without a neutral wire
- VERSATILE adjust settings without tools or the need to remove faceplate and wallplate
- PRACTICAL perfect for bathroom, basement, laundry room and spa

### **Technical Information**

**Product Features** 

Adjustment: Programmable

Color: White

Dimensions: W 1.73" X D 0.95" X H

4.13"

Grade: Residential

LED Color: Green and Red

Load Rating: 600W Incandescent, 300W LED/CFL, 400VA ELV, 400VA MLV, 1/4th HP Motor

Neutral: Optional

Power Consumption: <0.5 Watts

Sensor Type: Humidity Style Name: Decora

Switch: Relay

Switch Type: Single-Pole

Time Delay: 10, 20, 30 or 45 minutes

Voltage: 120 VAC Wallplate: Not Included Warranty: 5-Year Limited

Wiring: Ground or Neutral Required

Standards and Certifications

ASHRAE 62.2: Yes CALGREEN : Yes California Title 24: Yes

Standards and Certifications: CSA

#### **Features and Benefits**

- Ideal for Bathroom, basement, laundry room and home spa
- Replaces a single pole switch for control of a ventilation fan or fan/light combination
- Automatically detects excess humidity in a room and activates the ventilation fan to lessen condensation which helps reduce mold and mildew
- Helps reduce energy usage by automatically operating the fan only when needed
- For use with ventilation fans up to 1/4 HP
- Compatible with LED, CFL, Incandescent, Halogen, MLV and ELV lighting loads
- Can be connected to Neutral wire if Neutral is present in the wallbox; or to Earth ground if no Neutral wire is present in the wallbox
- Interchangeable line and load wires saving installation time
- Microprocessor control with digital sensing technology

- Zero Cross turn-on technology extends the life of switching relays
- Advanced sensing enhances detection when the room is occupied and minimizes false triggers when unoccupied
- Operating Modes for bath fan, air cycle and humidistat
- Test mode to help with sensor placement and setting adjustments
- Can be used to comply with the requirements of 2019/2022 California Title 24,
  Part 6, Indoor Air Quality and Mechanical Ventilation
- Complies with the requirements of 2019/2022 CALGREEN, Part II, Indoor Air Quality and Exhaust
- Meets requirements of ASHRAE 62.2
- Color change kits are available in Black, Brown, Gray, Ivory, Light Almond and White (DOSKT-00x)
- Five-Year Limited warranty

## SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:
JOB NUMBER:	

# Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

# Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

#### Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

### Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

### Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

