

2 A DESTRUCTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTE

THIS COPY IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF PANDUIT CORP.






NOTES:

PART NUMBER

- 1. UL LISTED AND CSA CERTIFIED
- 2. FOR COPPER WIRE ONLY.
- 3. DIMENSIONS IN BRACKETS ARE MILLIMETERS.
- 4. IF HEX KEY IS NOT GIVEN, FLAT HEAD SCREW IS USED.
- 5. SEE WWW.PANDUIT.COM FOR PACKAGE QUANTITIES







CERTIFIED

PANDU I T PART	CONDUCTOR RANGE	WIRE DIAMETER RANGE - IN	DIMENSIONS IN [mm]						WRENCH Size	TORQUE VALUE	RoHS COMPLIANT	
NUMBER	IMNOE		С	K	Н	L	Т	W	J	3125	IN-LBS	COWII LIANI
PNL - 4 - C	14 SOL - 4 STR	.064232	.27 [7]	.27 [7]	.56 [14]	1.25 [32]	.14 [3.57]	.53 [13]	5/16-24	SLOTTED SCREWDRIVER	45	YES
PNL1/0-L	8 SOL - 1/0 STR	.128375	.38 [10]	.33	.78 [20]	1.59 [40]	.14 [3.57]	.73 [16]	1/2-20	1/4"	200	YES
PNL-250-Q	6 SOL - 250 kcmil	.162575	.44 [11]	.39 [10]	1.05 [27]	1.97 [50]	.13 [3.17]	.94 [24]	5/8-18	5/16"	275	YES
PNL-500-3	4 SOL - 500 kcmil	.204815	.75 [19]	.53 [13]	1.47 [43]	3.00 [76]	.25 [6.35]	1.38 [35]	15/16-16	3/8"	375	YES
PNL-1000-3	500 kcmil - 1000 kcmil	.815-1.153	.69 [17]	.56 [14]	2.00	3.88 [99]	.38 [9.52]	1.75 [44]	1-3/8-14	1/2"	500	YES

							SEE TABLE					
							TITLE	CONE SCF			TOR - PNL SERIES	
							ITEM REVIS			JSTOMER DRA	WING	
							DATASET F	ILE NAME	'4BB/04 B-DC/04A		DANDIUT	
							Ţ		THI	RD ANGLE	PANDUIT	
04A	7-24-23	JHNU	JHNU	MRWA	C. REVISED DRAWING NUMBER: N41174BB-DC WAS C41174 B. ADDED ROHS COMPLIANT COLUMN A. CONVERTED TO NX	133002	MATERIAL	<u> </u>	/A	OJECTION	DRAWING NUMBER N41174BB-DC	
REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	DRAWN BY	10-96	снк Т М	NONE	SHEET 1 OF 1	
					Î							