



ON delay device, NTC thermistor, 100 ms, 220...230 V AC, 50/60 Hz

product designation	ON-delay timer for contactor	
design of the product	ON-delay timer	
General technical data		
product component protective wiring	No	
Substance Prohibittance (Date)	07/01/2006	
Ambient conditions		
ambient temperature		
• during operation	-20 ... +60 °C	
• during storage	-40 ... +80 °C	
Installation/ mounting/ dimensions		
mounting position	any	
fastening method	screw and snap-on mounting onto 35 mm DIN rail	
Connections/ Terminals		
type of electrical connection for auxiliary and control circuit	screw-type terminals	
Approvals Certificates		
General Product Approval	Declaration of Conformity	Marine / Shipping



other

[Confirmation](#)

Further information

Siemens has decided to exit the Russian market (see here).
<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>
 Siemens is working on the renewal of the current EAC certificates.
 Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).
Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>
Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3TX4180-0A>
Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3TX4180-0A>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3TX4180-0A>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3TX4180-0A&lang=en

last modified:

11/21/2022 