

Project	
Date	
Prepared By	
Model #	LT814840G9

Specifications ELECTRICAL

Watts: 16 watt system 14 watt lamp

Voltage: 120-277V 50/60Hz

Power Factor: 0.9

THD: 20%

Operating Temp. Range: -20°C to 45°C

Base Type: G13 Medium Bi-pin

LIGHT

Initial Lumens: 2200 Lumens per Watt: 157 Color Temperature: 4000K CRI: >82

AGENCY APPROVALS

DLC[®]: 5.1 UL/FCC: Yes RoHS/NSF: Yes

PRODUCT DETAILS

Diffuser Type: Internal coated glass tube Warranty: 10 years*

Fixture Rated Life: 50,000 hours Dimensions:

1" Diameter 48" Length



Norton Shores, Michigan 49441 T: 231.332.1188 | F: 231.726.5029 TOLL FREE: 866.632.7840 www.earthtronics.com

LED Linear Tube 48" Type A, 2200 Lumens, 14 Watt, 4000K



ORDER CODE: 11440 MODEL NUMBER: LT814840G9 LENGTH: 48 Inch Type A DLC PRODUCT ID: PLV8ZAR4PLXW

REBATE AVAILABILITY*

PRODUCT DESCRIPTION

14 watt EarthBulb LED linear tube is available in 4000K with 300 degree beam angle. Great light output and perfect for replacement of T8 fluorescent tubes. This linear tube provides 2200 lumens and has a CRI of 82. This lamp is engineered for high lumen maintenance over its 50,000 hour rated. Simply "plug and play" on electronic fluorescent ballasts. Compatible with instant start, program start, rapid start and dimmable T8 electronic ballast. Also compatible with fluorescent emergency ballasts. For use on Normal and Low Ballast Factor electronic ballasts only.* DLC[®] listed product.

PRODUCT FEATURES

- + 16 watt total system energy use when combined with a 0.88 BF ballast factor electronic T8 ballast per DLC test. 14 watt lamp energy use
- + DLC[®] technical requirement version 5.1
- + "Plug and play" on T8 systems utilizing instant start, rapid start, program start, emergency and dimming ballast
- + Provides 2200 lumens at 4000K 82CRI

- + May be used in enclosed fixtures
- + Suitable for damp locations
- + Always reference our ballast compatibility list before installation and use of this product
- + Ballast compatibility list may be found in the specification <u>here</u>
- + Glass tube construction provides maximum light out put and LED cooling

*Warranty void when lamp is used on high ballast factor electronics fluorescent ballast.

Please consult compatibility list https://www.earthtronics.com/product/2200-lumen-14-watt-type-a-48/. Rebate availability access it here: www.earthtronics.com/rebate-finder



LED Linear Tube 48"

Type A, 2200 Lumens, 14 Watt, 4000K

PACKAGE DETAILS

INDIVIDUAL PACKAGE

Individual Carton Oty: 1 Dimensions: 48" Length x 1.2" Width x 1.2" Height Weight: .53 lbs UPC: 840791114407

MASTER CARTON

Master Carton Oty: 25 Dimensions: 49.7" Length x 6.5" Width x 7.5" Height Weight: 14.4 lbs UPC: 84079111440700

LAMP BASETYPE



G13 Medium Bi-pin

Easily access our DLC qualified products with rebates in your area. ACCESS IT HERE: <u>Rebate Finder – Linear Tube</u> www.earthtronics.com/rebate-finder/catalog/



EarthTronics, Inc. | Norton Shores, MI 49441 | www.earthtronics.com | Email: contact@earthtronics.com Toll Free: 866.632.7840 Rev. 9.22.22 | ET11440