6GK7177-1MA20-0AA0





LOGO! CSM12/24 Compact Switch Module connection of a LOGO! (. ..0BA7/...0BA8) and up to 3 further nodes to Ind. Ethernet with 10/100 Mbit/s Unmanaged switch, 4 RJ45 ports, 1x front port for diagnostics DC 12/24V power supply LED diagnostics, LOGO! setup.

product type designation	LOGO! CSM 12/24
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / maximum configuration for modular devices	
number of electrical ports / maximum	4
interfaces / for communication / integrated	
number of electrical connections	
 for network components or terminal equipment 	4
number of 100 Mbit/s SC ports	
• for multimode	0
number of 1000 Mbit/s LC ports	
• for multimode	0
• for single mode (LD)	0
interfaces / other	
number of electrical connections	
for power supply	1
type of electrical connection	
for power supply	3-pole terminal block
supply voltage, current consumption, power loss	
type of voltage / 1 / of the supply voltage	DC
supply voltage / 1 / rated value	24 V
power loss [W] / 1 / rated value	1.5 W
 supply voltage / 1 / rated value 	10.2 30.2 V
 consumed current / 1 / maximum 	0.15 A
 type of electrical connection / 1 / for power supply 	3-pole terminal block
 product component / 1 / fusing at power supply input 	Yes
ambient conditions	
ambient temperature	
 during operation 	0 55 °C
 during storage 	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	90 %
protection class IP	IP20
design, dimensions and weights	
design	LOGO! module
width	71.5 mm
height	90 mm
depth	58.2 mm

net weight	0.15 kg
fastening method	
 35 mm top hat DIN rail mounting 	Yes
 wall mounting 	Yes
• S7-300 rail mounting	No
S7-1500 rail mounting	No
product functions / management, configuration, engineering	
product function	
multiport mirroring	No
product function / switch-managed	No
standards, specifications, approvals	
standard	
for safety / from CSA and UL	UL 508, CSA C22.2 No. 142
reference code	
 according to IEC 81346-2 	KF
 according to IEC 81346-2:2019 	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	ATEX: EN 60079-0 : 2009,EN 60079-15 :2010 (Directive 94/9/EC), IECEx: IEC
	60079-0 :2011, IEC 60079-15 :2010
• from CSA and UL	Haz-Loc ANSI/ISA 12.12.01: CL. I, Div2, Group A,B,C,D T4, CL I, Zone 2,
	Group IIC, T4, Ta=55°C
certificate of suitability	
 CCC / for hazardous zone according to GB standard 	Yes
CCC / for hazardous zone according to GB standard / as	Ex nA IIC T4 Gc
marking	
standards, specifications, approvals / other	
certificate of suitability	V
• C-Tick	Yes
KC approval	No
standards, specifications, approvals / marine classification	
Marine classification association	
 American Bureau of Shipping Europe Ltd. (ABS) 	No
 French marine classification society (BV) 	No
 Det Norske Veritas (DNV) 	No
Germanische Lloyd (GL)	No
Lloyds Register of Shipping (LRS)	No
 Nippon Kaiji Kyokai (NK) 	No
Polski Rejestr Statkow (PRS)	No No
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
security information	
security information	Siemens provides products and solutions with industrial security functions that
	support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

