

product type designation

product description



Support MDS 439E/U 589/RF380T

Support for mounting heat-resistant transponders on a crossbar

MOBY I/U/RF300 support for heat resistant data storage medium MDS 439E/MDS U589/RF380T short version 234x 140 without shrouding cover.

suitability for use

Transponders with a diameter of 114 mm can be mounted in the support

suitability for operation

for RF380T, MDS U589

mechanical data

material

V2A sheet

color

silver

ambient conditions

ambient temperature

- during operation -40 ... +220 °C
- during storage -40 ... +220 °C
- during transport -40 ... +220 °C

design, dimensions and weights

width

140 mm

height

2.5 mm

depth

234 mm

further information / internet links

internet link

- to website: TIA Selection Tool <http://www.siemens.com/tia-selection-tool>
- to the website: IWLAN <http://www.siemens.com/iwlan>
- to website: Industrial communication <http://www.siemens.com/ident/rfid>
- to website: Industry Mall <https://mall.industry.siemens.com>
- to website: Information and Download Center <http://www.siemens.com/industry/infocenter>
- to website: Selection guide for cables and connectors <https://sie.ag/2QdlxcP>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx-Download-Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <https://support.industry.siemens.com>

last modified:

8/29/2023 