




SIMATIC S7-400, rack aluminum UR2, central and distributed with 9 slots, 2 redundant PS can be plugged in

| General information                               |   |
|---|---|
| Product type designation                          | UR2   |
| Hardware configuration                            |   |
| Rack  |   |
| • Communication bus                               | Yes   |
| • P bus   | Yes   |
| Slots   |   |
| • Number of slots                                 | 9   |
| Standards, approvals, certificates                |   |
| CE mark   | Yes   |
| UKCA mark   | Yes   |
| UL approval                                       | Yes   |
| FM approval                                       | Yes   |
| RCM (formerly C-TICK)                             | Yes   |
| KC approval                                       | Yes   |
| EAC (formerly Gost-R)                             | Yes   |
| CCC   | Yes   |
| Ambient conditions                                |   |
| Ambient temperature during operation              |   |
| • min.  | 0 °C  |
| • max.  | 60 °C   |
| Ambient temperature during storage/transportation |   |
| • min.  | 0 °C  |
| • max.  | 70 °C   |
| Mechanics/material                                |   |
| rack profile material                             | aluminum  |
| Dimensions  |   |
| Width   | 257.5 mm  |
| Height  | 290 mm  |
| Depth   | 27.5 mm   |
| Weights   |   |
| Weight, approx.                                   | 1.5 kg  |
| last modified:                                    | 8/30/2023  |