

PIT es Set1s-5 s

400447



PITestop, E-STOP/contact block incl. surface mount housing, set consisting of E-STOP pushbutton with E-STOP symbol and logo and contact block with monitoring, 2 N/C, terminals (screw type).

Technical details

General data

Approval:	CE, UKCA, EAC (Eurasian), TÜV
Self-monitored:	yes

Technical data

Electrical data

Min. contact current:	1 mA
-----------------------	------

Emergency stop

Switch cap. E-STOP to standard:	EN 60947-5-1
Contact material E-STOP:	AgNi

Environmental data

Ambient temperature:	-25 - 55 °C
Pollution degree clear.&creep.:	3

Mechanical data

Mounting position:	any
Connection terminal:	Screw terminal
Height dimension:	72 mm
Width dimension:	103 mm
Depth dimension:	72 mm
Net weight:	161 g
Gross weight:	190 g

Environment	
RoHS directive:	2011/65/EU, 2015/863/EU
RoHS conformity:	yes
RoHS exceptions:	yes
RoHS except.s acc. to direct.:	6c
REACH compliance:	contains min. 1 SVHC-substance
REACH included substances:	Lead
%-part of the pollutant:	> 0,1
CAS No.:	7439-92-1
WEEE classification (08/2018):	5 devices (feed size < 50cm)
Commercial data	
Harmonized System Code:	85371098
ECLASS version:	ECLASS-9.1
ECLASS Reference Feature:	27371244
ETIM Version:	ETIM-7.0
ETIM Reference Group:	EG000017
ETIM Reference Feature:	EC002034