

Ordering data – Modular product system

Ordering table								Conditions	Code	Enter code
Size	32	40	50	63	80	100				
Module no.	8022569	8022585	8022601	574090	574091	574092				
Function	Electric cylinder								ESBF	ESBF
Drive type	Ball screw							[1]	-BS	
	Lead screw							[2]	-LS	
Size	32	40	50	63	80	100		-...		
Stroke [mm]	100								-...	
	200									
	300									
	400									
	30 ... 800	30 ... 800	30 ... 1000	30 ... 1200	30 ... 1500	30 ... 1500				
Spindle pitch [mm]	2.5	-	-	-	-	-		-...P		
	-	3	-	-	-	-				
	-	-	4	-	-	-				
	5	5	5	5	5	5				
	10	10	10	10	-	-				
	-	-	-	-	15	-				
	-	16	-	-	-	-				
	-	-	20	-	-	20				
	-	-	-	25	-	-				
	-	-	-	-	32	-				
	-	-	-	-	-	40				
Piston rod thread type	Male thread									
	Female thread								-F	
Degree of protection, electrical system	Standard									
	IP65								-S1	
Corrosion protection	Standard									
	High corrosion protection							[3]	-R3	
Special material properties	None									
	Recommended for production facilities for manufacturing lithium-ion batteries							[4]	-F1A	
Additional features	None									
	Food-safe as per supplementary material information							[5]	-F1	
Extended piston rod	None									
	1 ... 200								-...E	

[1] **BS** Only with spindle pitch 5P, 10P, 15P, 16P, 20P, 25P, 32P, 40P

[2] **LS** Only with spindle pitch 2.5P, 3P, 4P

[3] **R3** Only with S1

[4] **F1A** Not with S1
Not with LS
Not with R3
Not with F1

[5] **F1** Only with R3
Not with LS