

# US-EMLP-HA 30 (45X10) - Plastic label



0803878

<https://www.phoenixcontact.com/pc/products/0803878>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Plastic label, with bore hole, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: adhesive, lettering field size: 45 x 10 mm, Number of individual labels: 4



## Commercial data

Item number	0803878
Packing unit	10 pc
Minimum order quantity	10 pc
Product key	BG2419
Catalog page	Page 316 (C-3-2019)
GTIN	4055626173375
Weight per piece (including packing)	17.09 g
Weight per piece (excluding packing)	16.93 g
Customs tariff number	39199080
Country of origin	DE

# US-EMLP-HA 30 (45X10) - Plastic label



0803878

<https://www.phoenixcontact.com/pc/products/0803878>

## Technical data

### Product properties

Product type	Device marking
Product property	highly adhesive

### Marking

Number of individual labels	4
Number of individual labels per row	2

### Mounting

Mounting type	adhesive
---------------	----------

### Material specifications

RoHS compliant	yes
Foil strength	500 µm
Adhesive	Acrylic
Color	white
Material	PVC
Components	Silicone-free

### Environmental and real-life conditions

#### Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

#### UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

#### Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)

#### Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

#### Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

#### Ambient conditions

Ambient temperature (operation)	-30 °C ... 80 °C
---------------------------------	------------------

# US-EMLP-HA 30 (45X10) - Plastic label



0803878

<https://www.phoenixcontact.com/pc/products/0803878>

Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 %
Shelf life	12 months

## Dimensions

Width	46 mm
Length	47.5 mm
Material strength	0.63 mm

## Standards and regulations

Wipe resistance	DIN EN 61010-1 (VDE 0411-1)
-----------------	-----------------------------

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstraße 8  
D-32825 Blomberg  
+49 (0) 5235-3 00  
[info@phoenixcontact.com](mailto:info@phoenixcontact.com)