EM-DUO 120/15/GFI/AUX - Socket

5600639

https://www.phoenixcontact.com/in/products/5600639



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Rail-mounted dual power outlet with two 120 V AC/15 A receptacles equipped with ground fault circuit interruption (GFCI) for 35 mm DIN rail per EN 60715. GFCI protects against shock hazards associated with ground shorts. For enhanced safety, the grounding pin is located at the top to prevent shorting between the hot and neutral blades. Auxiliary terminals allow connection of auxiliary devices for protection by the GFCI outlet. Housing color: Ivory. National version: USA. Connection type: Screw.

Commercial data

Item number	5600639
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	****
Product key	BE7613
GTIN	4046356687973
Weight per piece (including packing)	320.4 g
Weight per piece (excluding packing)	261.4 g
Customs tariff number	85366990
Country of origin	US

EM-DUO 120/15/GFI/AUX - Socket

5600639

https://www.phoenixcontact.com/in/products/5600639



Technical data

Notes

Trade restriction	
CE note	The products are offered exclusively for export outside the EU and the European Economic Area.

Product properties

Product properties	
Product type	Socket
For country-specific use in	USA
	Canada
	Mexico
	Bahamas
	Bermuda
	Columbia
	Costa Rica
	Ecuador
	El Salvador
	Panama
	Puerto Rico
	Taiwan
	Venezuela
	Virgin Islands
Response time	25 ms (6 mA)

Electrical properties

Nominal voltage U _N	125 V AC
Nominal current I _N	15 A

Dimensions

Width	82 mm
Height	135 mm
Depth	49 mm

Material specifications

Color	ivory
Insulating material	Polycarbonate & ABS blend

Environmental and real-life conditions

Ambient conditions	
Degree of protection	IP20
Ambient temperature (operation)	-20 °C 60 °C

EM-DUO 120/15/GFI/AUX - Socket

5600639

https://www.phoenixcontact.com/in/products/5600639



Standards and regulations

Standards

Standards/regulations	UL 508
	UL 943
	CSA 22.2

Mounting

Connection method

Screw connection

Phoenix Contact 2023 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT (I) Pvt. Ltd. A-58/2, Okhla Industrial Area, Phase - II, New Delhi-110 020

+91.1275.71420 info@phoenixcontact.co.in