

Quality Products. Service Excellence.

Type 4, 4X Stainless Steel Pushbutton Enclosures 1437SS Series

Extra Deep











Application

- Designed to accept standard heavy duty oil tight pushbuttons, switches and pilot lights.
- Provides protection from dirt, dust, oil and water.

Standards

- UL 508A Type 4 and 4X
- CSA Enclosure 4 and 4X
- Complies with
 - o NEMA Type 4 and 4X
 - o IEC 60529, IP66
 - o JIC STD EGP-1-1967
- Appropriate components are required to maintain these standards.

Construction

- Formed from 14 gauge steel except A which is 16 gauge.
- · Smooth continuously welded seams.
- · Welded brackets provide for enclosure mounting.
- Captive cover screws fasten into threaded, sealed wells.
- Larger enclosures provide internally hinged removable covers, designed to hold the cover open during wiring (see table).
- · Oil resistant gasket and adhesive.
- A bonding stud is provided on the door and a grounding stud is provided on the enclosure.


Finish

• Natural stainless steel with a smooth brushed finish.

Accessories

- Hole Plugs
- Ground Wire Kits

· Pedestal and Base



	Part No.				No. Of								Overall Dimensions		Ship
304 SS 22.5mm	304 SS 30.5mm	316 SS 22.5mm	316 SS 30.5mm	Holes	Α	В	С	D	Е	F	G	L	W		Wt. lbs.
3647545 22245mm	3647 585 8 0.5mm	34875452£8 mm	3487 \$\$. \$6 . 15mm	Holes	4 ,Q 0	4 ® 0	4 ॡ 5	3 ქ 3	4 .5 0	2 ,9 6	3 & 5	5. <u>0</u> 00	4 \% 1	4.31	Wt.3bs.
1437MSSB	1437SSB	1437MS16B	1437S16B	2	6.00	4.00	4.75	3.13	6.50	2.96	5.25	7.00	4.31	6.31	4
1437MSSC	1437SSC	1437MS16C	1437S16C	3	8.00	4.00	4.75	3.13	8.50	2.96	7.25	9.00	4.31	8.31	5
1437MSSD	1437SSD	1437MS16D	1437S16D	4	10.00	4.00	4.75	3.13	10.50	2.96	9.25	11.00	4.31	10.31	5
-	1437SSS	-	1437S16S	16	11.75	10.75	4.75	9.88	12.25	9.71	11.00	12.75	11.06	12.06	10

¹ Not hinged

Data subject to change without notice

© 2017. Hammond Manufacturing Ltd. All rights reserved.