



# MASTER TL5 Circular



## MASTER TL5 Circular 22W/830 1CT/10

This circular TL5 lamp (tube diameter 16 mm) offers extended design possibilities. The slim tube allows the creation of extremely flat luminaires and enables omnidirectional light distribution. It is suitable for a wide range of professional and semi-professional applications, and is ideal for use in shops, offices and public areas with unconventional layouts.

### Warnings and Safety

- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data


General Information		Lamp Current (Nom)	
Cap-Base	2GX13 [2GX13]	0.300 A	
Flux measurement reference	Sphere	Controls and Dimming	
<b>Light Technical</b>		Dimmable	Yes
Color Code	830 [CCT of 3000K]	Mechanical and Housing	
Luminous Flux	1,800 lumen	Bulb Shape	C-T5 [C-T5 16 mm]
Color Designation	Warm White (WW)	Approval and Application	
Chromaticity Coordinate X (Nom)	0.44	Energy Efficiency Class	G
Chromaticity Coordinate Y (Nom)	0.403	Mercury (Hg) Content (Max)	4 mg
Correlated Color Temperature (Nom)	3000 K	Mercury (Hg) Content (Nom)	4 mg
Luminous Efficacy (rated) (Nom)	82 lm/W	Energy Consumption kWh/1000 h	24 kWh
Color rendering index (CRI)	81	EPREL Registration Number	423618
<b>Operating and Electrical</b>		Product Data	
Power Consumption	23.5 W	Full product code	871150064095625

# MASTER TL5 Circular

Order product name	MASTER TL5 Circular 22W/830 1CT/10
Order code	927965083013
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927965083013


Full product name	MASTER TL5 Circular 22W/830 1CT/10
EAN/UPC - Case	8711500640963
EAN/UPC - Product/Case	8711500640956

## Dimensional drawing




Product	D (max)	D (min)	E (min)	E (max)	I (min)	I (max)
MASTER TL5 Circular 22W/830 1CT/10	18 mm	14 mm	220 mm	230 mm	187 mm	197 mm

## Photometric data




Spectral Power Distribution Colour - MASTER TL5 Circular 22W/830 1CT/10

## Lifetime




Life Expectancy Diagram - MASTER TL5 Circular 22W/830 1CT/10



Life Expectancy Diagram - MASTER TL5 Circular 22W/830 1CT/10

# MASTER TL5 Circular

## Lifetime



Lumen Maintenance Diagram - MASTER TL5 Circular 22W/830 1CT/10

