



UPC Code : 078477264287

Country Of Origin : China

RoHS Compliant : Yes

DT160-1LW

Decora In-Wall 60-Minute Countdown Timer Switch, 15A, ½ HP/9.8A Fan/Motor, Single Pole

The Decora 60-Minute Countdown Timer Switch has 5 buttons with 10-minute, 20-minute, 30-minute and 60-minute preset time options and a manual off button. Single Pole, 600W LED/CFL, 1800W Incandescent/Halogen, 1200VA Magnetic Low Voltage/Electronic Low Voltage/Fluorescent, ½ HP/9.8A Fan/Motor, 15A Resistive. Can be installed with or without a neutral wire, wallplate sold separately - White

- CONVENIENT – replace your current wall switch with a countdown timer to automate fan/motor loads and lights. Four preset time buttons, press to turn on and automatically turns off when time expires
- EASY DIY INSTALL – slim depth for easier fit in wall box, interchangeable line and load wires to help prevent miswiring, and a Green Flex Sleeve that connects to a ground wire, or to a neutral wire when the sleeve is removed
- ENERGY SAVING – ensure lights and fans are not left on unintentionally
- PRACTICAL – for bathroom exhaust fans, lights, heat lamps, towel warmers, attics, garages, basements
- STYLISH – easily change the color using DTKIT faceplates available in white, ivory, light almond, gray, black and brown

Technical Information

Product Features

Amperage : 15 A

Brand : Decora

Color : White

Compatible Bulb Type : LED , CFL , Incandescent , Halogen , Magnetic Low Voltage , Electronic Low Voltage , Fluorescent , Fan , Motor

Device Type : Timer Switch

Faceplate Colors : White , Ivory , Light Almond , Gray , Black , Brown

Function : Single-Pole (SP)

Grade : Residential

Grounding : Yes

Horsepower Rating : 1/2 HP

Mounting Type : In-Wall

Neutral Required : Optional

Optional Faceplates : DTKIT

Power Consumption : <1 Watt

Standards and Certifications : CSA , FCC , IC

Style : Push Button

Termination : Leads

Timer Options : 60-Minute (10M, 20M, 30M, 60M)

Timer Type : Countdown

Voltage : 120 VAC

Wallplate : Not Included

Warranty : 5-Year

Wattage Rating : 600W , 1800W , 1200VA

Features and Benefits

- Replace a standard wall switch with a countdown timer to ensure exhaust fans or lights are not left on unintentionally
- Four preset time option buttons 10-20-30-60 min with separate off button. Press time option to turn on and will automatically turn off when time expires
- 600W LED/CFL, 1800W Incandescent/Halogen, 1200VA Magnetic Low Voltage, 1200 VA Electronic Low Voltage, 1200 VA Fluorescent, ½ HP/9.8 Amp Fan/Motor, 15A Resistive

- Shallow design easily fits in the wallbox and lead terminal wires for easier installation without having to bend wires around terminal screws
- Innovative Green Flex Sleeve wires to ground in homes with no neutral wiring or remove the sleeve and connect to a neutral wire if present in the wallbox. A ground wire is required for installation
- DIY friendly with two black wires that can be interchanged between line and load to help prevent miswiring
- Zero Cross turn-on technology to extend the life of the switch
- Manual override keeps load on for 24 hours. Override can be disabled by pressing one of the timer option buttons or off button
- Change color with DTKIT faceplates available in white, ivory, light almond, gray, black and brown (sold separately)
- Ideal to use for bathroom exhaust fans, heat lamps, towel warmers, garages, attics, basements and more
- Do not use to control lights if there is no other light source in the space

Patents*

N_A

*This list is provided for patent marking purposes only. A good faith effort is made to maintain the accuracy and completeness of this list. No legal inference should be drawn from the omission of a patent from this list.

SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 95%; height: 20px;" type="text"/>	CATALOG NUMBERS: <input style="width: 60%; height: 20px;" type="text"/> <input style="width: 35%; height: 20px;" type="text"/>	
JOB NUMBER: <input style="width: 95%; height: 20px;" type="text"/>	<input style="width: 25%; height: 20px;" type="text"/>	<input style="width: 25%; height: 20px;" type="text"/>

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
 Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday):
 +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 ·
 FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2021 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to:
www.leviton.com/international/contacts/

