

Grinding/Sanding/Polishing

Angle Grinder

1,400 W SJS Angle Grinder, Soft Start, Paddle Switch



318	9564PC	9565PC	9566PC
Continuous rating Input	1,400W	1,400W	1,400W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")	150 mm (6")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	12,000	12,000	10,000
Dimensions (L x W x H)	307 x 129 x 103 mm (12-1/8 x 5-1/8 x 4")	307 x 139 x 103 mm (12-1/8 x 5-1/2 x 4")	307 x 169 x 103 mm (12-1/8 x 6-5/8 x 4")
Net weight	2.4 - 2.7 kg (5.3 - 6 lbs.)	2.4 - 3.5 kg (5.3 - 7.7 lbs.)	2.4 - 2.8 kg (5.3 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,400 W SJS Variable Speed Angle Grinder, Soft Start, Slide Switch



318	9565CLR	9565CVL
Continuous rating Input	1,400W	1,400W
Wheel Diameter	125 mm (5")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	2,000 - 7,800	2,000 - 7,800
Dimensions (L x W x H)	311 x 125 x 114 mm (11-3/8 x 5 x 4-1/2")	311 x 80 x 114 mm (12-1/4 x 3-5/32 x 4-1/12")
Net weight	2.1 - 2.6 kg (4.6 - 5.8 lbs.)	2.1 - 2.6 kg (4.6 - 5.9 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)



9565CLR:
Anti-restart function

Abrasive disc, Pad, Head cover, Side grip, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Paddle Switch



260	GA4050	GA4550	GA5050
Continuous rating Input	1,300W	1,300W	1,300W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Hole Diameter	16 mm (5/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 117 x 100 mm (12-3/4 x 4-5/8 x 4-5/16")	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)	2.4 - 2.8 kg (5.3 - 6.2 lbs.)	2.5 - 2.8 kg (5.5 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Paddle Switch



260	GA4552	GA5052
Continuous rating Input	1,300W	1,300W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.4 - 2.8 kg (5.3 - 6.2 lbs.)	2.5 - 2.8 kg (5.5 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Anti-Restart Function, Paddle Switch



260	GA4050R	GA4550R	GA5050R
Continuous rating Input	1,300W	1,300W	1,300W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Hole Diameter	16 mm (5/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 117 x 100 mm (12-3/4 x 4-5/8 x 4-5/16")	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)	2.4 - 2.8 kg (5.3 - 6.2 lbs.)	2.5 - 2.8 kg (5.5 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Anti-Restart Function, Paddle Switch



260	GA4552R	GA5052R
Continuous rating Input	1,300W	1,300W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.4 - 2.8 kg (5.3 - 6.2 lbs.)	2.5 - 2.8 kg (5.5 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Anti-Restart Function, Paddle Switch, Undetachable Wheel Cover



260 mm	GA4051R	GA4551R	GA5051R
Continuous rating Input	1,300W	1,300W	1,300W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")
Hole Diameter	16 mm (5/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 117 x 100 mm (12-3/4 x 4-5/8 x 4-5/16")	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.3 - 2.5 kg (5.1 - 5.5 lbs.)	2.4 - 2.7 kg (5.3 - 6.0 lbs.)	2.5 - 2.7 kg (5.5 - 6.0 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,300 W Angle Grinder, Anti-Restart Function, Paddle Switch, Undetachable Wheel Cover



260 mm	GA4553R	GA5053R
Continuous rating Input	1,300W	1,300W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000
Circumference of grip portion	212 mm (8-3/8")	212 mm (8-3/8")
Dimensions (L x W x H)	325 x 130 x 117 mm (12-3/4 x 5-1/8 x 4-5/8")	325 x 140 x 117 mm (12-3/4 x 5-1/2 x 4-5/8")
Net weight	2.4 - 2.7 kg (5.3 - 6.0 lbs.)	2.5 - 2.7 kg (5.5 - 6.0 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,100 W SJS II Angle Grinder, Anti-Restart Function, Mechanical Brake, Soft Start, Slide Switch



325 mm	GA4541R	GA5041R
Continuous rating Input	1,100W	1,100W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000
Dimensions (L x W x H)	325 x 130 x 121 mm (12-3/4 x 5-1/8 x 4-3/4")	325 x 140 x 121 mm (12-3/4 x 5-1/2 x 4-3/4")
Net weight	2.7 - 3 kg (5.9 - 6.6 lbs.)	2.7 - 3.8 kg (5.9 - 8.4 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,100 W SJS II Angle Grinder, Anti-Restart Function, Soft Start, Slide Switch



325 mm	GA4540R	GA5040R	GA6040R
Continuous rating Input	1,100W	1,100W	1,100W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")	150 mm (6")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000	9,000
Dimensions (L x W x H)	303 x 130 x 116 mm (11-7/8 x 5-1/8 x 4-9/16")	303 x 140 x 116 mm (11-7/8 x 5-1/2 x 4-9/16")	303 x 171 x 116 mm (11-7/8 x 6-3/4 x 4-9/16")
Net weight	2.4 - 2.8 kg (5.4 - 6.1 lbs.)	2.5 - 3.6 kg (5.4 - 8 lbs.)	2.5 - 2.9 kg (5.5 - 6.4 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,100 W SJS II Angle Grinder, Slide Switch



325 mm	GA4040	GA4540	GA5040	GA6040
Continuous rating Input	1,100W	1,100W	1,100W	1,100W
Wheel Diameter	100 mm (4")	115 mm (4-1/2")	125 mm (5")	150 mm (6")
Hole Diameter	16 mm (5/8")	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	11,000	11,000	11,000	9,000
Dimensions (L x W x H)	303 x 117 x 111 mm (11-7/8 x 4-5/8 x 4-3/8")	303 x 130 x 116 mm (11-7/8 x 5-1/8 x 4-9/16")	303 x 140 x 116 mm (11-7/8 x 5-1/2 x 4-9/16")	303 x 171 x 116 mm (11-7/8 x 6-3/4 x 4-9/16")
Net weight	2.2 - 2.5 kg (4.9 - 5.6 lbs.)	2.3 - 2.7 kg (5.2 - 5.9 lbs.)	2.4 - 3.5 kg (5.2 - 7.8 lbs.)	2.4 - 2.8 kg (5.3 - 6.2 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)



Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

125 mm (5") 1,100 W SJS Angle Grinder, Anti-Restart Function, Soft Start, Slide Switch



325 mm	9565HR
Continuous rating Input	1,100W
Wheel Diameter	125 mm (5")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	12,000
Dimensions (L x W x H)	299 x 140 x 111 mm (11-3/4 x 5-1/2 x 4-3/8")
Net weight	2.4 - 3.5 kg (5.2 - 7.6 lbs.)
Power supply cord	2.5 m (8.2 ft)




Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Grinding/Sanding/Polishing

Angle Grinder

1,100 W SJS Angle Grinder, Slide Switch



325 	9564H	9565H
Continuous rating Input	1,100W	1,100W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	2,800 - 12,000	12,000
Dimensions (L x W x H)	299 x 129 x 103 mm (11-3/4 x 5-1/16 x 4")	299 x 139 x 103 mm (11-3/4 x 5-1/2 x 4")
Net weight	2.3 - 2.6 kg (5.1 - 5.7 lbs.)	2.3 - 3.4 kg (5.1 - 7.5 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)




Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,100 W SJS Angle Grinder, Paddle Switch



325 	9564P	9565P
Continuous rating Input	1,100W	1,100W
Wheel Diameter	115 mm (4-1/2")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	12,000	12,000
Dimensions (L x W x H)	307 x 129 x 103 mm (12-1/8 x 5-1/8 x 4")	307 x 139 x 103 mm (12-1/8 x 5-1/2 x 4")
Net weight	2.4 - 2.7 kg (5.3 - 5.9 lbs.)	2.4 - 2.7 kg (5.3 - 5.9 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)




Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,050 W SJS Angle Grinder, Large Trigger Switch



303 	GA5021	GA5011	GA6021
Continuous rating Input	1,050W	1,050W	1,050W
Wheel Diameter	125 mm (5")	125 mm (5")	150 mm (6")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	10,000	12,000	10,000
Dimensions (L x W x H)	384 x 139 x 120 mm (15-1/8 x 5-1/2 x 4-3/4")	384 x 139 x 113 mm (15-1/8 x 5-1/2 x 4-7/16")	384 x 172 x 120 mm (15-1/8 x 6-3/4 x 4-3/4")
Net weight	2.7 - 3.9 kg (6 - 8.6 lbs.)	2.6 - 3.8 kg (5.8 - 8.4 lbs.)	2.8 - 3.2 kg (6.1 - 7.1 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)




Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

1,050 W SJS Angle Grinder, Finger Trigger Switch



303 	GA5020	GA5010	GA6020	GA6010
Continuous rating Input	1,050W	1,050W	1,050W	1,050W
Wheel Diameter	125 mm (5")	125 mm (5")	150 mm (6")	150 mm (6")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")	22.23 mm (7/8")
No Load Speed (RPM)	12,000	12,000	10,000	10,000
Dimensions (L x W x H)	356 x 139 x 120 mm (14 x 5-1/2 x 4-3/4")	356 x 139 x 112 mm (14 x 5-1/2 x 4-3/8")	356 x 169 x 120 mm (14 x 6-5/8 x 4-3/4")	356 x 169 x 112 mm (14 x 6-5/8 x 4-3/8")
Net weight	2.7 - 3.9 kg (6 - 8.6 lbs.)	2.6 - 3.8 kg (5.8 - 8.4 lbs.)	2.8 - 3.2 kg (6.1 - 7.1 lbs.)	2.7 - 3.1 kg (5.9 - 6.9 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)	2.5 m (8.2 ft)




Depressed center wheel, Side grip, Wheel cover, Lock nut wrench

Angle Grinder

125 mm (5") 1,400 W Angle Grinder, Soft Start, Slide Switch, X-LOCK

GA5080R: Anti-Restart Function



318 	GA5080	GA5080R
Continuous rating Input	1,400W	1,400W
Wheel Diameter	125 mm (5")	125 mm (5")
Hole Diameter	22.23 mm (7/8")	22.23 mm (7/8")
Max cutting depth	31 mm (1-1/4")	31 mm (1-1/4")
No Load Speed (RPM)	12,000	12,000
Circumference of grip portion	205 mm (8-1/8")	205 mm (8-1/8")
Dimensions (L x W x H)	309 x 141 x 113 mm (12-1/8 x 5-9/16 x 4-7/16")	309 x 141 x 113 mm (12-1/8 x 5-9/16 x 4-7/16")
Net weight	2.5 - 3.6 kg (5.5 - 7.9 lbs.)	2.5 - 3.6 kg (5.5 - 7.9 lbs.)
Power supply cord	2.5 m (8.2 ft)	2.5 m (8.2 ft)




Depressed center wheel, Side grip, Wheel cover

Angle Grinder

115 mm (4-1/2") 840 W Angle Grinder, Slide Switch, X-LOCK



325 	GA4570
Continuous rating Input	840W
Wheel Diameter	115 mm (4-1/2")
Hole Diameter	22.23 mm (7/8")
No Load Speed (RPM)	11,000
Circumference of grip portion	195 mm (7-5/8")
Cutting depth	26 mm (1")
Dimensions (L x W x H)	288 x 131 x 112 mm (11-3/8 x 5-1/8 x 4-3/8")
Net weight	2.2 - 2.5 kg (4.9 - 5.5 lbs.)
Power supply cord	2.5 m (8.2 ft)



Grinding wheel, Side grip, Wheel cover