

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more. For commercial applications in which 24/7 use is required, use model FMLRL.

CONSTRUCTION

Features a white acrylic diffuser and is available in 11" and 20" sizes. Hidden cam-latches provide easy diffuser removal for installation and maintenance.

OPTICS

11" units produce 1400 lumens and 20" units produce 4000 lumens, all at 30,000 hours life.

ELECTRICAL

Fixture operates at 120 volts, 60 Hz. 70 lumens per watt.

20" Standard input = 44 watts, 90 lumens per watt.

Works with most standard incandescent dimmers (see list of approved dimmers).

INSTALLATION

All mounting hardware included.

LISTINGS

cUL Certified to US and Canadian standards and listed suitable for damp locations. Select items are ENERGY STAR® certified.

WARRANTY

5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/support/warranty/terms-and-conditions

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Catalog Number	
Notes	
Туре	

Decorative Indoor

Residential LED Low Profile Round



HIGH-PERFORMANCE LED



Specifications		
	11"	20"
Diameter:	11 (27.9)	20 (5.8)
Depth:	3.25 (8.3)	4 (10.2)
Weight:	1 lbs (.5 kg)	4.4 lbs (2 kg)

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options.**

Series	Module/CRI	Color temperature
FMLRDL 11IN 11" Residential LED low profile round flush mount 1 FMLRDL 20IN 20" Residential LED low profile round flush mount	148 >80 358 >80	40 4000 K

Notes
1 FMLRDL 11 14840 is not ENERGY STAR certified.

Example: FMLRDL 11 14840

LIGHTING FACTS

lighting facts	S® DE
Light Output (Lumens)	3970
Watts	44
Lumens per Watt (Efficacy)	90.23
Color Accuracy Color Rendering Index (CRI)	80
Light Color Correlated Color Temperature (CCT) 4000 (B	right White)
Warm White Bright White 2700K 3000K 4500K	Daylight 6500K
All results are according to IESNA LM-79-2008: Approved Meth Photometric Testing of Solid-State Lighting, The U.S. Departmet product test data and results.	
Visit www.lightingfacts.com for the Label Re	ference Guide.
Registration Number: NJSM-BGJT1M (10/17/2016)	

The FMLRDL is designed to operate with most standard Triac
Based dimmers and is not compatible with 0-10v dimming sys-
tems. The following is a list of dimmers tested and does not imply
any guarantee or warranty of compatibility with a particular
application. Unlisted dimmers do not imply non-compatibility.

SUGGESTED DIMMERS

Part number(s)
CT-600P/CT-603P
DV-600P/DV-603P
CTCL-153P
DVCL-153P
AYCL-153P
DVELV-300P
R50-IPL06
6615-P
HCL453PTCCCV6

PHOTOMETRICS

Full photometric data report available two weeks from request. Consult factory.