JUNO

Project:

Fixture Type:

Location:

Contact/Phone:

PRODUCT DESCRIPTION

TC Remodel Housing designed for use in non-insulated areas • Shallow housing construction allows for fit in 2 x 6 construction • Juno Type TC fixtures are designed for installations where housing and J-Box will not come into contact with insulation • Blinking light after installation indicates that improper bulb or trim is being used or that fixture has been improperly covered with insulation • In U.S., insulation must be spaced 3" away from the housing and J-Box • TC Remodel Housing for remodel application where back side of ceiling is not accessible • Installs through an opening in the ceiling from below

• Secured in place by factory installed screw driven remodel clamps for easy installation into ceiling material.

PRODUCT SPECIFICATIONS

Lamp Lamp ratings based on trim selected - see reverse.

Socket Detachable medium base porcelain with nickel-plated copper screw shell.

Trims Trim selection shown on reverse.

Labels UL/cUL listed for U.S. and Canada through-branch wiring and damp locations • Product thermally protected against improper use of insulation • UL/cUL Listed • Trim No. 11, 12, 12SQ, 4101, 4102, V4012 and V4041 are wet location approved for covered ceiling applications • Trims 14, 17, 17SQ, V4017 and V4034 are wet location approved for covered ceiling applications, when used with outdoor rated lamps.

Testing All reports are based on published industry procedures; field performance may differ from laboratory performance.

Specifications subject to change without notice.

INSTALLATION

Junction Box Pre-wired junction box, UL/cUL listed for throughbranch wiring maximum 4 No. 12 AWG 90° C branch circuit conductors (2 in, 2 out) • Junction box provided with removable access plate, (5) ½" knockouts, (4) Non-metallic sheathed cable connectors and ground wire • Knockouts equipped with pryout slots • Supplied with push-in electrical connectors for fast installation.

Housing TC housing, 22-gauge steel with white finish
Remodel clamps provided with #2 Quadrex drive screws (#2 Robertson/#2 Phillips combo) • Clamps accommodate up to a 5/8" ceiling thickness.

PRODUCT CODES


Catalog No.		Input Voltage	Lamp Types
TCIRC W N	4" Incandescent Remodel Clamp Style Non-IC Housing	120V	PAR2O/PAR16 Medium Base, MR16/PAR16/ES16 GU10 Base (See reverse for Trim/Lamp/Max. Wattage Ratings)


Housing and trim can be ordered together or separate, but will always ship separately.



TC1RC

DIMENSIONS





4 3/8" CEILING CUTOUT

Description	
GU10 Socket Whip	
4" Housing Locator	
	GU10 Socket Whip

To order, specify catalog number

4" TC REMODEL HOUSING INCANDESCENT LAMPS

G3.1.12 4" TC REMODEL HOUSING INCANDESCENT LAMPS TC1RC

ROUND TRIMS/ L	AMPS		
	Cat. No.	Description	Max. Lamp Rating
\bigcirc	13 WH	4" Downlight Pinhole with Integral Shield Trim - White	50W PAR20
	14 BWH ♦♦	4" Downlight Baffle Trim - Black Baffle, White Trim Ring	
	14 BSC ♦♦	4" Downlight Baffle Trim - Black Baffle, Satin Chrome Trim Ring	50W PAR20
	14 BBRZ ♦♦	4" Downlight Baffle Trim - Black Baffle, Bronze Trim Ring	3000 mill20
	14 BBL ♦♦	4" Downlight Baffle Trim - Black Baffle, Black Trim Ring	
	14 WWH ♦♦	4" Downlight Baffle Trim - black ballle, black trim king 4" Downlight Baffle Trim - White Baffle, White Trim Ring	
	14 00011 0 0		
	17 CWH ♦♦	4" Downlight Cone Trim - Clear Alzak® Cone, White Trim Ring	50W PAR20
	17 GWH ♦♦	4" Downlight Cone Trim - Gold Cone, White Trim Ring	
	17 BWH ♦♦	4" Downlight Cone Trim - Black Cone, White Trim Ring	
	17 PTSC ++	4" Downlight Cone Trim - Pewter Cone, Satin Chrome Trim Ring	
	17 WWH ♦♦	4" Downlight Cone Trim - White Cone, White Trim Ring	
	17 HZWH ♦♦	4" Downlight Cone Trim - Haze Cone, White Trim Ring	
	17 WHZWH ♦♦	4" Downlight Cone Trim - Wheat Haze Cone, White Trim Ring	
	17 WHZBRZ ♦♦	4" Downlight Cone Trim - Wheat Haze Cone, Bronze Trim Ring	
•	10 WH	4" Flush Gimbal Ringed - White	50W PAR20
	10 BL	4" Flush Gimbal Ringed - Black	
(\bigcirc)	10 SC	4" Flush Gimbal Ringed - Satin Chrome	
\smile	10 BRZ	4" Flush Gimbal Ringed - Bronze	
\frown	18 WH	4" Adjustable Mini Eyeball Trim - White	60W PAR16
\bigcirc	18 SC	4" Adjustable Mini Eyeball Trim - Satin Chrome	60000 Marco
n D	440 WH	4" Adjustable Flush Gimbal Ring Trim - White	50W MR16, PAR16,
	440 BL	4" Adjustable Flush Gimbal Ring Trim - Black	ES16 120V GU10 Base
I I I I I I I I I I I I I I I I I I I	440 SC	4" Adjustable Flush Gimbal Ring Trim - Satin Chrome	(Requires GU 10WHIP)
	440 BRZ	4" Adjustable Flush Gimbal Ring Trim - Bronze	
	445 WH	4" Adjustable Slot Aperture Trim - White	50W MR16, PAR16 ES16 120V GU10 Base, (Requires GU10WHIP)
\bigcirc	448 WH	4" Adjustable Eyeball with Black Baffle Trim - White	50W MR16, PAR16
	448 SC	4" Adjustable Eyeball with Black Baffle Trim - Satin Chrome	ES16120V GU10 Base
			(Requires GU 10WHIP)
\bigcirc	11 WH ♦	4" Lensed Drop Opal Trim - White	50W PAR20
	12 WWH ♦	4" Frosted Lens with Clear Center Trim - Perimeter Frosted Lens , Classic Aged Bronze Trim Ring	50W PAR20
\bigcirc	12 WSC 🔶	4" Frosted Lens with Clear Center Trim - Perimeter Frosted Lens, Satin Chrome Trim Ring	
	12 WBRZ 🔶	4" Frosted Lens with Clear Center Trim - Perimeter Frosted Lens, Bronze Trim Ring	
	446 WH	4" Wall Wash Adjustable Scoop Trim - White	50W MR16, PAR16 ES16 120V GU10 Base, (Requires GU10WHIP)
	4101 WH 🔶	4" Decorative Beveled Dome Lens Trim - White	50W PAR20
\bigcirc	4101 SC 🔶	4" Decorative Beveled Dome Lens Trim - Satin Chrome	
	4101 BRZ 🔶	4" Decorative Beveled Dome Lens Trim - Bronze	
	4102 WH ♦	4" Decorative Beveled Lensed Trim - White	50W PAR20
	4102 SC 🔶	4" Decorative Beveled Lensed Trim - Satin Chrome	
	4102 BRZ 🔶	4" Decorative Beveled Lensed Trim - Bronze	
\frown	4103 FROSTWH	4" Decorative Beveled Cylinder Trim - Frosted Glass, White Trim Ring	50W PAR20
\bigcirc	4103 FROSTSC	 Decorative Beveled Cylinder Trim - Frosted Glass, White Trim King 4" Decorative Beveled Cylinder Trim - Frosted Glass, Satin Chrome Trim Ring 	JUWYTAKZU
\bigcirc			
\bigcirc	4104 HZSC	4" Decorative Beveled Cone Trim - Haze Cone, Satin Chrome Trim Ring	50W PAR20
\bigcirc	4104 WHZBRZ	4" Decorative Beveled Cone Trim - Wheat Haze Cone, Bronze Trim Ring	
	4150 MESHSC	4" Decorative Glass Cylinder Trim - Mesh Glass, Satin Chrome Trim Ring	50W PAR20
Y			

G3.1.12 4" TC REMODEL HOUSING INCANDESCENT LAMPS TC1RC

SQUARE TRIMS/ LAMPS

Cat. No.	Description	Max. Lamp Rating
175Q BWH ♦♦ 175Q WWH ♦♦ 175Q HZWH ♦♦ 175Q WHZWH ♦♦	4" Square Downlight Trim - Black, White Trim Ring 4" Square Downlight Trim - White, White Trim Ring 4" Square Downlight Trim - Haze, White Trim Ring 4" Square Downlight Trim - Wheat Haze, White Trim Ring	50W PAR20
13SQ WH	4" Square Pinhole Trim - White	50W PAR20
4405Q WH 4405Q BL	4° Square Flush Gimbal Trim - White 4° Square Flush Gimbal Trim - Black	50W MR16 120V GU10 Base (Requires GU10WHIP, 35°Vertical Adjustment)
125Q WWH ♦	4^{\ast} Sqaure Frosted Lens with Clear Center Trim - White, White Trim Ring	50W PAR20

VULITE TRIMS/ LAMPS

	Cat. No. V4034 BWH ♦♦	Description 4" Baffle - Black, White Trim Ring	Max. Lamp Rating 50W PAR20
	V4034 WWH ♦♦	4" Baffle - White, White Trim Ring	
	V4017 CWH ♦♦	4" Cone - Clear Alzak, White Trim Ring	50W PAR20
	V4010 WH V4010 BN	4° Gimbal Ring - White Trim Ring 4° Gimbal Ring - Brushed Nickel Trim Ring	50W PAR20
	V4018 WH	4" Eyeball - White Trim Ring	60W PAR16
	V4012 WH	4" Stippled Opal Lens Shower With Reflector - White Trim Ring	50W PAR20
	V4040 WH V4040 BN	4° Gimbal Ring - White Trim Ring 4° Gimbal Ring - Brushed Nickel Trim Ring	50W MR16 PAR16, ES16 120V GU10 Base (Requires GU10WHIP)
	V4041 WH	4" Stippled Lens Ring - White Trim Ring	50W MR16 PAR16, ES16 120V GU10 Base (Requires GU10WHIP)
	V4048 WH	4" Low Voltage Eyeball with Baffle \cdot White Trim Ring	SOW MR16 PAR16, ES16 120V GU10 Base (Requires GU10WHIP)
	GU10WHIP	GU10 Socekt Whip	
◆ UL Listed for u	use in wet location.		Trim Size: 5" O.D. Alzak is a registered trademark of Alcoa Corp.

 \blacklozenge UL Listed for use in wet location with outdoor rated lamp.

Trim Size: 5" O.D. Alzak is a registered trademark of Alcoa Corp. Note: In Canada when insulation is present, Type IC fixtures must be used.