SIEMENS

Data sheet

6GK1901-0DB30-6AA8

product type designation

product description

suitability

IE FC M12 Plug PRO (PROFINET)

M12-Connector with high protection, 8-pole, X-coded

Industrial Ethernet FastConnect M12 plug PRO 4x 2 M12 plug-in connector with Rugged metal enclosure and FC connection method, with axial cable outlet (Xcoded) 1 pack=8 units for SCALANCE W.



y for use	For connecting electrical cables to SCALANCE W (M12 gigabit interface) for
	fast assembly with the FastConnect system

	last assembly with the rastconnect system	
transfer rate		
transfer rate / for Industrial Ethernet	10 Mbit/s, 100 Mbit/s, 1000 Mbit/s, 10000 Mbit/s	
interfaces		
number of electrical connections		
 for Industrial Ethernet FC TP cables 	8	
 for network components or terminal equipment 	1	
type of electrical connection		
 for Industrial Ethernet FC TP cables 	integrated cut-and-clamp contacts for 8-wire TP FC installation cable AWG24	
 for network components or terminal equipment 	M12 connector (X-coded)	
type of electrical connection / FastConnect	Yes	
mechanical data		
material / of the enclosure	metal	
locking mechanism design	Screwed joint	
tightening torque / for M12 round connector / maximum	0.6 N·m	
connector coding / of the M12 circular connector	X	
design, dimensions and weights		
type of cable outlet	180° cable outlet	
width	16.8 mm	
height	16.8 mm	
depth	52 mm	
net weight	40 g	
connectable cable cross-section	6.5 8 mm	
connectable conductor cross-section	0.21 0.33 mm²	
ambient conditions		
ambient temperature		
 during operation 	-40 +85 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
chemical resistance		
• to water	resistant	
protection class IP	IP65/67	
product features, product functions, product components / general		
product feature		
 PoE capability 	Yes	

• silicon-free

PoE+capability

Yes

Yes

product component	
strain relief	Yes
standards, specifications, approvals	
certificate of suitability	
 RoHS conformity 	Yes
 UL approval 	Yes
 cULus approval 	Yes
 railway application in accordance with EN 50155 	Yes
 fire protection in accordance with EN 45545-2 	Yes
standard for structured cabling	Cat6A
further information / internet links	
internet link	
 to web page: selection aid TIA Selection Tool 	http://www.siemens.com/tia-selection-tool
 to website: Industrial communication 	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
 to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
• to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
to website: Image database	http://automation.siemens.com/bilddb
• to website: CAx-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 8/29/2023 🖸