


LOCTITE® BRAND **GASKETING** AND **SEALING** PROPERTIES CHART

PRODUCT	Item Number	Container	Color	Oil Resistance	Non-Corrosive	Temperature Range (Intermittent)	Sealing Time	Agency Approvals
Instant <b>Gasket</b>	30684 30509 30507	4 oz. can 5 oz. cartridge 7 oz. can	Black	Increased oil resistance	Non-corrosive	-75 to 500°F (-59 to 260°C)	Operating strength 15 psi -1 min.	GM 998-5990 Type I, Ford WSE-M4G323-A6, DaimlerChrysler MS-GF44 Grade A, CFIA
<b>Superflex®</b> RTV	59330 59375 30563 59530 59575 30562 59430 59475 82518	80 ml tube 300 ml cartridge 8 oz. can 80 ml tube 300 ml cartridge 8 oz. can 80 ml tube 300 ml cartridge 8 oz. can	Black Black Black Clear Clear Clear White White White	-	-	-65 to 450°F (-54 to 232°C)	Tack free - 30 min. Full strength - 24 hrs.	UL Classified for U.S., ULC Classified for Canada, NSF/ANSI 51, CFIA
<b>Superflex®</b> Blue RTV	30560 30533 30541 30518	80 ml tube 300 ml cartridge 8 oz. can 12 oz. tube	Blue	-	-	-65 to 500°F (-54 to 260°C)	Tack free - 30 min. Full strength - 24 hrs.	-
<b>Superflex®</b> Red High Temp RTV	59630 59675 30564 82279	80 ml tube 300 ml cartridge 8 oz. can 12 oz. tube	Red	-	-	-75 to 600°F (-59 to 316°C)	Tack free - 30 min. Full strength - 24 hrs.	CFIA
<b>Superflex®</b> Non-Corrosive RTV	51387 51388	80 ml tube 300 ml cartridge	Clear	Oil resistant	-	-75 to 500°F (-59 to 260°C)	Tack free - 25 min. Full strength - 24 hrs.	UL Classified for U.S.,
<b>598™</b> Black	34018 59830 59875 59866 59891	0.5 oz. tube 70 ml tube 300 ml cartridge 8.75 oz. can 49 lb. pail	Black	Excellent oil resistance	Non-corrosive	-75 to 625°F (-59 to 329°C)	Tack free - 30 min. Full strength - 24 hrs.	ABS, CFIA
<b>587™</b> Blue	58730 58775 30567 58791	70 ml tube 300 ml cartridge 8.75 oz. can 17 liter pail	Blue	Increased oil resistance	Non-corrosive	-75 to 500°F (-59 to 260°C)	Tack free - 30 min. Full strength - 24 hrs.	UL Classified for U.S., NSF P1, CFIA, ABS
<b>5920™</b> Copper	30542 82046	70 ml tube 300 ml cartridge	Copper	Increased oil resistance	Non-corrosive	-65 to 700°F (-54 to 371°C)	Tack free - 60 min. Full strength - 24 hrs.	-
<b>5699™</b> Grey	18718 18581	70 ml tube 300 ml cartridge	Grey	Increased oil resistance	Non-corrosive	-75 to 625°F (-59 to 329°C)	Tack free - 30 min. Full strength - 24 hrs.	-
<b>Aviation Gasket Sealant</b>	30517 30516	0.25 pt. brush can 1 pt. brush can	Dark reddish brown	Oil resistant	Non-corrosive	-65 to 400°F (-54 to 204°C)	Full strength - 12 hrs.	CFIA
<b>Gasket Sealant 1</b>	30510 30511 30512	1.5 oz. tube 3 oz. tube 7 fl. oz. tube	Reddish brown	Oil resistant	Non-corrosive	-65 to 400°F (-54 to 204°C)	Full strength - 24 hrs.	CFIA
<b>Gasket Sealant 2</b>	30513 30514 30515 80964	1.5 oz. tube 3 oz. tube 7 fl. oz. tube 5 gal. can	Black	Oil resistant	Non-corrosive	-65 to 400°F (-54 to 204°C)	Remains tacky	-
<b>Hi-Tack Gasket Sealant</b>	30524 30525 30526	0.25 pt. brush can 1 pt. brush can 9 oz. aerosol	Red	Increased oil resistance	Non-corrosive	-65 to 500°F (-54 to 260°C) Aerosol to 600°F	5 min. to set	-
<b>QuickStix™ 534™</b> Hi-Tack <b>Gasket Dressing</b> 	39155 39156 39157	9 gm stick 19 gm stick 38 gm stick	Purple	Oil resistant	Non-corrosive	-65 to 300°F (-54 to 149°C)	5 min. to set	-
<b>Copper Gasket Adhesive</b>	30535	9 oz. aerosol	Copper	Oil resistant	Non-corrosive	-50 to 500°F (-45 to 260°C)	Remains tacky	-
<b>High Temperature Gasket Maker</b>	30558	7 fl. oz. tube	Black	Oil resistant	Non-corrosive	-50 to 600°F (-45 to 315°C)	3-5 hours to set	CFIA