



KAPO350, 350 Kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.

By Burndy
Catalog # [KAPO350](#)

350 Kcmil pin adaptor, Torque: 500 N lb, Voltage: 600 V.



Features

- AL9CU Dual Rated for both copper and aluminum conductor
- Listed to UL Wire Connector Standard UL486A-486B
- Rated for use with Fine Strand Conductor
- 600 Volt Rated
- Range Taking conductor port
- Plastisol insulated covers provided with each connector

Application

Terminate "upsized" conductor and/or fine strand conductor into mechanical connectors found in molded case circuit breakers, panel board equipment, and other switchgear.

General

Connector Type	Offset
EU RoHS Indicator	Contact Manufacturer
Hex Key	3/8 in
Installation Torque Recommended in-lb	450
Material	Aluminum
Sub Brand	Pin Adaptor
Type	1/0 - 350 Mechanical Pin Adaptor; Off-Centered Pin
UPC	621945493360

Dimensions

Dimension - Strip Length inch	1.11 in
Dimensions	2.75 in x 1.50 in x 2.00 in
Height	2.00 in
Length	2.75 in
Outside Diameter	1.38 in
Width	1.50 in

Electrical Ratings

Amperage Rating	350 A
-----------------	-------

Conductor Related

Conductor - AL Str Size Range	1/0 AWG - 350 kcmil
Conductor - Copper DLO Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Flex H Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Flex I Size Range	#6 - 1/0 AWG
Conductor - Copper Flex K Size Range	1/0 AWG - 350 kcmil
Conductor - Copper Str Size Range	1/0 AWG - 350 kcmil
Conductor Size	1/0 AWG- 350 KCMIL

Logistics

Carton Quantity	25
Minimum Pack Quantity	1
Pallet Quantity	2250

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[Sales Drawings - 50076514](#)



A proud member of the Hubbell Family.

©2023 Hubbell Incorporated. All rights reserved.
BRDY-KAPO350-SPEC-EN | REV 8/2023