

PROVO PART NUMBER
996505

**PLENUM MULTI-CONDUCTOR - FOIL SHIELD
STRANDED TINNED COPPER CONDUCTORS
CONDUCTORS TWISTED
100% ALUMINUM FOIL SHIELD
STRANDED TINNED COPPER DRAIN WIRE
PLENUM PVC INSULATION • PLENUM PVC JACKET**



SPEC CRITERIA	SPECIFICATION
AWG	18
STRANDING	7 x 26
NUMBER OF CONDUCTORS	5
DRAIN WIRE SIZE	20
INSULATION TYPE	PLENUM PVC
INSULATION THICKNESS	0.008
JACKET TYPE	PLENUM PVC
JACKET THICKNESS	0.016
NOM. CABLE OD	0.198
VOLTAGE	300
TEMPERATURE	+75°C
PUT-UP METERS	300 / 150
WEIGHT (LBS)	44 / 22
CSA	CMP, FT-6
UL	CMP C22.2, UL444
RoHS	COMPLIANT
FLAME TEST	FT-6
COLOUR CODE	Black / White / Red / Green / Orange

©2022 PROVO LTD.

Provo makes every reasonable effort to ensure their accuracy at the time of this publication. Information and specifications herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability. The information provided is correct to the best of Provo's knowledge, and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes part of. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. All sales of Provo products are subject to Provo's standard terms and conditions of sale.