

## TERMINALS & CONNECTORS (K-SPEC® SERIES)



### Crimp 'N' Shrink Butt Connectors (K-Spec® Series)

600V Rating, 105°C, Copper



#### 22-18GA



Approximate length of tubing:  
1.250"

691244	5 pk
561244	100 pk
561244J	300 pcs/Jar
561244D	500 pk

#### 16-14GA



Approximate length of tubing:  
1.250"

691245	5 pk
561245	100 pk
561245J	300 pcs/Jar
561245D	500 pk

#### 12-10GA



Approximate length of tubing:  
1.500"

691246	5 pk
561246	100 pk
561246J	200 pcs/Jar
561246D	500 pk



B

### PVC Insulated Butt Connectors (K-Spec® Series)

300V Rating, 75°C, Brass



#### 22-18GA



691231	11 pk
561231	100 pk
561231D	500 pk

#### 16-14GA



691232	10 pk
561232	100 pk
561232D	500 pk

#### 12-10GA



691233	7 pk
561233	100 pk
561233D	500 pk

### PVC Insulated Ring Terminals (K-Spec® Series)

600V Rating, 75°C, Copper



#### 22-18GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"	Stud Size 3/8"
691000	691002	691003	561004	561005	561006
100 pk	100 pk	11 pk	100 pk	100 pk	100 pk
561000D	561002D	561003D	561004D	561005D	561006D
500 pk	500 pk	500 pk	500 pk	500 pk	500 pk

#### 16-14GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"	Stud Size 3/8"
691016	691018	691019	691020	561021	691022
11 pk	11 pk	10 pk	9 pk	100 pk	7 pk
561016	561018	561019	561020	561021	561022
100 pk	100 pk	100 pk	100 pk	100 pk	100 pk
561016D	561018D	561019D	561020D	561021D	561022D
500 pk	500 pk	500 pk	500 pk	500 pk	500 pk

#### 12-10GA



Stud Size #6	Stud Size #8	Stud Size #10	Stud Size 1/4"	Stud Size 5/16"
691032	561033	691034	691035	561036
7 pk	100 pk	7 pk	6 pk	100 pk
561032	561033D	561034	561035	561036D
100 pk	500 pk	100 pk	500 pk	500 pk
561032D		561034D	561035D	
500 pk		500 pk	500 pk	



Stud Size 3/8"	Stud Size 1/2"
691037	691038
6 pk	6 pk
561037	561038
100 pk	100 pk
561037D	561038D
500 pk	500 pk

Crimp Tools can be found on pages E-6 – E-7

## TERMINALS & CONNECTORS (K-SPEC® SERIES)



### PVC Insulated Spade/Fork Terminals (K-Spec® Series)

600V Rating, 75°C, Copper



Crimp Tools can be found on pages E-6 – E-7

#### 22-18GA



Stud Size #6  
**561048** 100 pk  
**561048D** 500 pk



Stud Size #8  
**561049** 100 pk  
**561049D** 500 pk



Stud Size #10  
**561050** 100 pk  
**561050D** 500 pk

#### 16-14GA



Stud Size #6  
**561061** 100 pk  
**561061D** 500 pk



Stud Size #8  
**561062** 100 pk  
**561062D** 500 pk



Stud Size #10  
**691063** 9 pk  
**561063** 100 pk  
**561063D** 500 pk



Stud Size 1/4"  
**561064** 100 pk  
**561064D** 500 pk

#### 12-10GA



Stud Size #6  
**561074** 100 pk  
**561074D** 500 pk



Stud Size #8  
**561075** 100 pk  
**561075D** 500 pk



Stud Size #10  
**691076** 7 pk  
**561076** 100 pk  
**561076D** 500 pk



Stud Size 1/4"  
**561077** 100 pk  
**561077D** 500 pk

### Fully Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)

300V Rating, Brass, Nylon (105°C), PVC (75°C)



#### 22-18GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561354** 100 pk  
**561354D** 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561353** 100 pk  
**561353D** 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
**561345** 100 pk  
**561345D** 500 pk

#### 16-14GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561357** 100 pk  
**561357D** 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561358** 100 pk  
**561358D** 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
**561346** 100 pk  
**561346D** 500 pk

#### 12-10GA



Female quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561623** 100 pk  
**561623D** 500 pk



Male quick disconnect, Fully Insulated (Nylon). Tab Size .250" x .032"  
**561621** 100 pk  
**561621D** 500 pk



Female quick disconnect, Fully Insulated (PVC). Tab Size .250" x .032"  
**561347** 100 pk  
**561347D** 500 pk

## TERMINALS & CONNECTORS (K-SPEC® SERIES)



### PVC Insulated Quick Disconnects/Slide Connectors (K-Spec® Series)



300V Rating, 75°C, Brass  
**22-18GA**



Female quick disconnect  
Tab Size .110" x .020"  
**561377** 100 pk  
**561377D** 500 pk



Male quick disconnect  
Tab Size .110" x .020"  
**561378** 100 pk  
**561378D** 500 pk



Female quick disconnect  
Tab Size .110" x .032"  
**561379** 100 pk  
**561379D** 500 pk



Male quick disconnect  
Tab Size .110" x .032"  
**561380** 100 pk  
**561380D** 500 pk



Female quick disconnect  
Tab Size .187" x .020"  
**561381** 100 pk  
**561381D** 500 pk



Male quick disconnect  
Tab Size .187" x .020"  
**561382** 100 pk  
**561382D** 500 pk



Female quick disconnect  
Tab Size .187" x .032"  
**561383** 100 pk  
**561383D** 500 pk



Male quick disconnect  
Tab Size .187" x .032"  
**561384** 100 pk  
**561384D** 500 pk



Female quick disconnect  
Tab Size .205" x .020"  
**561395** 100 pk  
**561395D** 500 pk



Female quick disconnect  
Tab Size .250" x .032"  
**561352** 100 pk  
**561352D** 500 pk



Male quick disconnect  
Tab Size .250" x .032"  
**561351** 100 pk  
**561351D** 500 pk

### 16-14GA



Female quick disconnect  
Tab Size .110" x .020"  
**561396** 100 pk  
**561396D** 500 pk



Male quick disconnect  
Tab Size .110" x .020"  
**561391** 100 pk  
**561391D** 500 pk



Female quick disconnect  
Tab Size .110" x .032"  
**561397** 100 pk  
**561397D** 500 pk



Female quick disconnect  
Tab Size .187" x .020"  
**561387** 100 pk  
**561387D** 500 pk



Male quick disconnect  
Tab Size .187" x .020"  
**561388** 100 pk  
**561388D** 500 pk



Female quick disconnect  
Tab Size .187" x .032"  
**561389** 100 pk  
**561389D** 500 pk



Male quick disconnect  
Tab Size .187" x .032"  
**561390** 100 pk  
**561390D** 500 pk



Female quick disconnect  
Tab Size .205" x .020"  
**561398** 100 pk  
**561398D** 500 pk



Female quick disconnect  
Tab Size .250" x .032"  
**691355** 11 pk  
**561355** 100 pk  
**561355D** 500 pk



Male quick disconnect  
Tab Size .250" x .032"  
**691356** 10 pk  
**561356** 100 pk  
**561356D** 500 pk



Female quick disconnect  
Tab Size .312" x .032"  
**561399** 100 pk  
**561399D** 500 pk



Female quick disconnect  
Tab Size .375" x .047"  
**561400** 100 pk  
**561400D** 500 pk

### 12-10GA



Female quick disconnect  
Tab Size .250" x .032"  
**692093** 6 pk  
**562093** 100 pk  
**562093D** 500 pk



Male quick disconnect  
Tab Size .250" x .032"  
**692115** 7 pk  
**562115** 100 pk  
**562115D** 500 pk



Female quick disconnect  
Tab Size .375" x .047"  
**561401** 100 pk  
**561401D** 500 pk

*Crimp Tools can be found on pages E-6 – E-7*

B