

# K-SPEC® CABLE TIES

## Standard Nylon Cable Ties (General Purpose)

- Material with Pure Nylon 6.6, UL 94V-2, Operation temp. -40°C~+85°C (-40°F ~+185°F)
- Suggested Installation temp. -10°C~+85°C (14°F~185°F)
- Products listed with:



A



**RoHS PAHs Reach**



	Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.
M	E4180C	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4180M	Black	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E4189C	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	100
	E4189M	Natural	2.5 [.095]	100 [4.0]	20.5 [0.80]	8 [18]	1000
	E6180C	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6180M	Black	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E6189C	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	100
	E6189M	Natural	2.5 [.095]	150 [6.0]	36.5 [1.43]	8 [18]	1000
	E8180C	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8180M	Black	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E8189C	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	100
	E8189M	Natural	2.5 [.095]	200 [8.0]	52.5 [2.06]	8 [18]	1000
	E14180C	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100
	E14180M	Black	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000
E14189C	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	100	
E14189M	Natural	2.8 [.110]	380 [15.0]	109.8 [4.32]	8 [18]	1000	
I	E5400C	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5400M	Black	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E5409C	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	100
	E5409M	Natural	3.6 [.014]	140 [5.5]	33.0 [1.30]	18 [40]	1000
	E8400C	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8400M	Black	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E8409C	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	100
	E8409M	Natural	3.6 [.014]	200 [8.0]	52.5 [2.06]	18 [40]	1000
	E11400C	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11400M	Black	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E11409C	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	100
	E11409M	Natural	3.6 [.014]	280 [11.0]	78.0 [3.07]	18 [40]	1000
	E14400C	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100
	E14400M	Black	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000
E14409C	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	100	
E14409M	Natural	3.6 [.014]	370 [14.5]	106.0 [4.17]	18 [40]	1000	

NEW  
NEW  
NEW

### K-Spec® Part No. Instructions:

**E20175**



Pack Qty	Code
50	L
100	C
500	D
1000	M

Colour	Code	Colour	Code
Natural	9	Blue*	6
White*	WH	Purple*	7
UVB Resistant Black	0	Gray*	8
Brown*	1	FL. Orange*	16
Red*	2	FL. Yellow*	17
Orange*	3	FL. Green*	18
Yellow*	4	FL. Blue*	20
Green*	5		

\* 100,000 Piece Minimum Order for Coloured Ties

# K-SPEC® CABLE TIES

## Standard Nylon Cable Ties (General Purpose)

**A**

	Part no.	Colour	Width mm [Inch]	Length mm [Inch]	Max Bundle Diameter mm [inch]	Min Loop Tensile Kgs [lb]	Std. Pk. Qty.	
S	E5500C	Black	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	100	NEW
	E5500M	Black	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	1000	NEW
	E5509C	Natural	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	100	NEW
	E5509M	Natural	4.6 [.181]	120 [4.7]	23.8 [0.93]	22 [50]	1000	NEW
	E7500C	Black	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	100	
	E7500M	Black	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	1000	
	E7509C	Natural	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	100	
	E7509M	Natural	4.8 [.189]	200 [8.0]	49.5 [1.94]	22 [50]	1000	
	E11500C	Black	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	100	
	E11500D	Black	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	500	
	E11509C	Natural	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	100	
	E11509D	Natural	4.8 [.189]	300 [11.8]	81.0 [3.18]	22 [50]	500	
	E14500C	Black	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	100	
	E14500D	Black	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	500	
	E14509C	Natural	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	100	
	E14509D	Natural	4.8 [.189]	370 [14.5]	103.5 [4.07]	22 [50]	500	
	E17500C	Black	4.8 [.189]	430 [17.0]	122.5 [4.82]	22 [50]	100	
	E17509C	Natural	4.8 [.189]	430 [17.0]	122.5 [4.82]	22 [50]	100	
	E24500C	Black	4.8 [.189]	610 [24.0]	179.9 [7.08]	22 [50]	100	NEW
	E24509C	Natural	4.8 [.189]	610 [24.0]	179.9 [7.08]	22 [50]	100	NEW
E36500C	Black	4.8 [.189]	920 [36.0]	278.6 [10.97]	22 [50]	100	NEW	
E36509C	Natural	4.8 [.189]	920 [36.0]	278.6 [10.97]	22 [50]	100	NEW	
HD	E81200C	Black	7.6 [.300]	220 [8.6]	57.2 [2.25]	55 [120]	100	
	E81209C	Natural	7.6 [.300]	220 [8.6]	57.2 [2.25]	55 [120]	100	
	E111200C	Black	7.6 [.300]	300 [11.8]	82.8 [3.25]	55 [120]	100	
	E111209C	Natural	7.6 [.300]	300 [11.8]	82.8 [3.25]	55 [120]	100	
	E141200C	Black	7.6 [.300]	380 [15.0]	108.0 [4.25]	55 [120]	100	
	E141209C	Natural	7.6 [.300]	380 [15.0]	108.0 [4.25]	55 [120]	100	
	E181200L	Black	7.6 [.300]	450 [18.0]	130.5 [5.13]	55 [120]	50	NEW
	E181209L	Natural	7.6 [.300]	450 [18.0]	130.5 [5.13]	55 [120]	50	NEW
	E201200L	Black	7.6 [.300]	540 [21.0]	159.0 [6.25]	55 [120]	50	NEW
	E201209L	Natural	7.6 [.300]	540 [21.0]	159.0 [6.25]	55 [120]	50	NEW
	E221200C	Black	7.6 [.300]	550 [21.6]	162.5 [6.39]	55 [120]	100	
	E221209C	Natural	7.6 [.300]	550 [21.6]	162.5 [6.39]	55 [120]	100	
	E241200L	Black	7.6 [.300]	610 [24.0]	181.5 [7.14]	55 [120]	50	NEW
	E241209L	Natural	7.6 [.300]	610 [24.0]	181.5 [7.14]	55 [120]	50	NEW
	E301200L	Black	7.6 [.300]	750 [29.5]	226.1 [8.90]	55 [120]	50	NEW
E301209L	Natural	7.6 [.300]	750 [29.5]	226.1 [8.90]	55 [120]	50	NEW	