

# Screws

AERIAL  
INSTALLATION

## LAG SCREWS

Lag Screws of 1/4", 3/8" and 1/2" diameter have upset shoulders. Hot-dip galvanized.



**Gimlet Point Type**



**Fetter Drive, Drive-Point**



**Twist-Drive Pilot Point**



**B-Cable Suspension Screw**



**Fetter Drive Pilot-Point Type**



**Hex Head Lag Screw with Neoprene-Steel Washer**

| Gimlet Point Type                             |                   |        |                           |
|---|-------------------|--------|---------------------------|
| Catalog Number                                | Dimensions Inches |        | Approx Ship Wt Each (lbs) |
|   | Diameter          | Length |                           |
| 872112GP                                      | 1/4               | 1 1/2  | 0.02                      |
| 8722GP  | 1/4               | 2      | 0.03                      |
| 872212GP                                      | 1/4               | 2 1/2  | 0.04                      |
| DF1L3   | 1/4               | 3      | 0.06                      |
| DF3L3   | 3/8               | 3      | 0.09                      |
| Twist-Drive Pilot Point Type                  |                   |        |                           |
| 508500  | 1/2               | 4      | 0.23                      |
| PSC2050562                                    | 1/2               | 4 1/2  | 0.26                      |
| Fetter Drive Pilot-Point Type                 |                   |        |                           |
| DF6L250                                       | 3/8               | 2 1/2  | 0.07                      |
| 508743  | 3/8               | 3      | 0.10                      |
| 508744  | 3/8               | 4      | 0.13                      |
| 508753  | 1/2               | 3      | 0.20                      |
| 508754  | 1/2               | 4      | 0.24                      |
| 50875412                                      | 1/2               | 4 1/2  | 0.27                      |
| 508755  | 1/2               | 5      | 0.28                      |
| B-Cable Suspension Screw                      |                   |        |                           |
| PSC2170146                                    | 7/8               | 4 1/2  | 1.87                      |
| Hex Head Lag Screw with Neoprene-Steel Washer |                   |        |                           |
| PSC2050504                                    | 1/4               | 2      | 0.03                      |
| PSC2050631                                    | 1/4               | 2 1/2  | 0.04                      |