



BOLT, SPOOL, SINGLE-UPSET, 5/8in x 16in

By CHANCE Utility
Catalog # [PS7745](#)

Spool bolts are used to support a spool insulator in the horizontal position in secondary applications. Industry slang is Upset Bolt.



*Representative Image

Features

- 6" thread length and cone pointed end
- Overall length is 20-3/4"
- Includes one square nut with cotter key
- Rated cantilever load is 1,900 lbs.
- Hot dip galvanized per ASTM A-153
- Manufactured in compliance with ANSI C135.31
- RUS listed, q - Bolt, double upset

General

Coating	Galvanized, ASTM A-153
Material	Steel
Tensile Strength	12400 lb.
Type	Spool Bolts
UPC	096359520382

Dimensions

Diameter	0.63 in
Diameter (Fraction)	5/8 in
Distance From Pole	N/A
Length	16.00 in
Weight	1.9 lb

Logistics

Carton Quantity	20
Pallet Quantity	800

Product Assets

[Catalogs - Pole Line Hardware](#)
[Sales Drawings - Upset Spool Bolts Single And Double \(SA7740\)](#)

Related Products

6805 - WASHER, ROUND, 11/16in HOLE, 1 3/4in DIA.
 6813 - WASHER, SQ FLAT, 5/8in SIZE, 2 1/4in
 3512 - MF TYPE CURVED LOCK NUT, 5/8in THREAD
 C2050186 - SPRING WASHER, REGULAR-DUTY DOUBLE-COIL, 5/8in SIZE



A proud member of the Hubbell Family.