

FLUORESCENT LAMPHOLDERS MEDIUM BI-PIN G13 FOR T-8 / T-12 LAMPS

E9

FL005 SERIES Low Profile Turn Type Lampholders

<p>T-8 T-12</p>	<p>G13</p>	<ul style="list-style-type: none"> - White polycarbonate body, rated 110°C - Turn lock type, low profile - Quick connect push-in wire terminals for 18 AWG solid wire 5/16" - Two wire ports per terminal for easy harness wiring - For a 0.023" - 0.040" (0.6 mm - 1.0 mm) panel thickness 	<ul style="list-style-type: none"> - Available shunted for use with instant start electronic ballasts; saves time and makes wiring easier - Many models to choose from - Rated 660W, 600V, suitable for all new HO lamps - cCSAus Certified / cULus Listed
---------------------	------------	--	--

<p>FL005 FL005-WN FL005-WS</p>	<p>PANEL CUTOUTS Standard Push-In</p>	<p>FL005* Solid Shoulder, Standard Profile</p>
--	--	--

FL005-C*Δ Solid Shoulder with Captive Nut

FL005-S* Solid Shoulder Shunted

FL005-SC* Shunted with Captive Nut

FL005-W* Flexible Snap-in Shoulder

FL005-WC*Δ Flexible Snap-in Shoulder, Captive Nut

FL005-WN* Snap-in Shoulder with Locating nib

FL005-WS* Flexible Snap-in Shoulder, Shunted

FL005-WSC* Flexible Snap-in Shoulder, Shunted Captive Nut

* Add "-S" after product code for internal shunted version Δ Screws are packed separately.
Also available assembled, add Suffix "-A" after "C" in part number.

FOR MORE INFORMATION PLEASE CALL 1-800-661-9610 (HEAD OFFICE) 1-888-762-5384 (USA)

PLEASE CONSULT THE FACTORY FOR MORE PRODUCTS AND CUSTOMIZATION.
PRODUCT DETAILS AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.



LINEAR FLUORESCENT LAMPHOLDERS

T-8
T-12