

Angle Grinder LXT®

DGA519Z

18V • 125 mm • 3 000 – 8 500 min⁻¹

The X-LOCK mechanism allows the installation / removal of X-LOCK discs without the need for a tool.

With X-Lock, one click is all you need. Insert the wheel into the X-Lock bracket and press it into place. To replace the wheel, simply pull the lever and remove wheel. The X-Lock allows you to change wheels quickly and easily - without the need for a key and even when wearing gloves. Tool only, battery and charger not included.



TECHNICAL SPECIFICATIONS

Nominal Battery Voltage	18 V
Voltage LXT	✓
Brushless Motor	✓
Battery protection	✓
No load speed	3000 - 8500 min ⁻¹

Max. Depth of Cut	29 mm
Grinding Disc Diameter	125 mm
Anti-Restart Function (NVR Switch)	✓
Dead Man's Switch (No Lock-On)	✓
Electronic brake	✓
Grip AVT	✓
Grinding Wheel	✓
Sound Pressure Level (L _{pA})	80 dB(A)

Noise Uncertainty (K Factor)	3 dB(A)
Vibration Level (3 axes)	5,5 m/s ²
Vibration Uncertainty (K Factor)	1,5 m/s ²
Tool weight with battery (EPTA)	2,7 - 3 kg

EAN 0088381893510

Link to Product page - www.makita.ae



USER BENEFITS

- Brushless maintenance-free and long-life motor
- disc brake
- Paddle switch



RELATED PRODUCTS

OPTIONAL ACCESSORIES

196845-3

Dust collecting cover 125 mm, Ø



E-00365

Grinding disc X-Lock, 115 x 6,0 mm,



E-00387

Cutting disc X-Lock, 115 x 1,2 mm,



E-00393

Grinding disc X-Lock, 125 x 6,0 mm,



E-00418

Cutting Disc X-Lock, 125 x 1,2 mm



E-02076

Diamond wheel 125 mm, X-LOCK

