

Lawn Mover LXT®

DLM532PT4

18V X2 • 53 cm • 70 L

Strong steel frame driven cordless lawnmower.

Strong steel frame Driving and bio-cutting, collecting, side discharge cordless lawnmower. Centralized cutting height adjustment and ball-bearing wheels, cutting width 53 cm. Infinitely variable speed control, load sensing and four battery bay, recommended cutting area of 2,300 m².



 **36V** **LXT** **BL MOTOR** **SOFT NO LOAD**

Technical specifications

Voltage LXT	✓
Nominal Battery Voltage	2 x 18 V
Battery Chemistry (Ni-Cd / Ni-MH / Li-ion)	Li-ion
Cutting height positions	10
Width of Mowing Deck	53,4 cm
Mowing area	2 300 m ²
Mowing Height	20 - 100 mm
Rear Wheel Diameter	23 cm
Front Wheel Diameter	23 cm
RPM (Soft no load mode)	2300 / 2800 min ⁻¹
Collecting Box Capacity	70 L
Propelling Speed	2,5 - 5,0 km/h
Self-Propelled	✓
Sound Power Level (L _{WA})	91,9 dB(A)
Sound Pressure Level (L _{pA})	80,9 dB(A)

User benefits

- Shower-proof construction, IPX4
- Battery protection circuit protects against overloading, over-discharging and over-heating

EAN 0088381894593

Link to product - www.makita.com



Related products

Standard AC

327589-6
Rod, 6 Mm



459887-1
Side Discharge Mouth



782210-8
Socket Wrench 17



782212-4
Socket Wrench 13 mm



Standard MA

BL1850B (4x)
Battery LXT® 5,0 Ah



DC18RD
Battery Charger LXT®



Optional AC

191D50-1
Swing back blade 530



Other

[User manual](#)

[Parts drawing](#)