

250 minutes continuous run time

Ergonomically designed handle with sure grip

Cutting depth adjustment: 15/20/25 mm



Dual blade action Stain-free grass shear blade

Surface of glittering silver features high anti-abrasion for long lasting coating.



Tool-less blade change system

- Grass shear blade can be removed / installed without tool.
- Hedge trimmer blade can be removed / installed by using a coin to loosen / tighten two screws.









Accessories

Hedge trimmer accessories

Hedge trimmer blade Chip receiver Part No.198408-1 (200mm(7-7/8"))



Part No. 195267-4

Grass shear accessories Grass shear blade






Grass receiver 160

Part No. 457426-1

Blade cover Part No.451816-0









Long handle attachment with wheel (option)

Enables to use the machine comfortably in a standing posture.

- 5 stage angle adjustment allows for grip height adjustment according to user's height.
- · Lock-off button operable from both left and right side





Li-ion Rattery & Charging Time Reference Compatibility Chart

Li-ion battery & charging rime Reference, Compatibility Chart						
*with Battery fuel gauge	BL1815N	*BL1820B	*BL1830B	*BL1840B	*BL1850B	*BL1860B
	18V 1.5Ah	18V 2.0Ah	18V 3.0Ah	18V 4.0Ah	18V 5.0Ah	18V 6.0Ah
DC18RC	15	24	22 min	36	45	55
for 18V	min	min		min	min	min
DC18SD for 18V	30 min	45 min	60 min	90 min	110 min	130 min

DUM604 160 mm (6-5/16") 160 mm (6-5/16") 15, 20, 25 mm (9/16", 13/16", 1") **Cutting Width** Depth Adjustment Strokes Per Minute (SPM) Continuous Use (min.) 2,500 with BL1860B / BL1850B/ BL1840B / BL1830B/BL1820B/BL1815N: 250/200/160/125/80/60 76 dB(A) 2.5 m/s² or less Sound Pressure Level Vibration Level 337x177x131mm (13-1/4"x7"x5-1/8") Dimensions (L x W x H) Net weight 1.4 - 1.8 kg(3.2-3.9lbs) Standard Equipment: Grass Receiver, Blade Cover, Battery, Charger

Cordless Grass Shear

ltems of standard equipment and specifications may vary by country or area. The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heavi-est combination, according to EPTA-Procedure 01/2014, are shown in the table.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan