

Eaton DH1-354D5FB-C54C

Catalog Number: DH1-354D5FB-C54C

Eaton PowerXL DH1 VFD,4.5A,3 HP,2.2 kW,525 - 600 Vac,KEYPAD,EMC Filter,DC Choke,Brake Chopper,IP54



General specifications

Product Name	Catalog Number
Eaton PowerXL DH1 variable frequency drive	DH1-354D5FB-C54C
	UPC
	786689049201
Product Length/Depth	Product Height
12 in	7.91 in
Product Width	Product Weight
6.02 in	14.33 lb
Warranty	Compliances
Eaton Selling Policy 25-000 generally applies with some exceptions. Drive products come with a standard 24 months from date of shipment and 36 months with Eaton certified start up all inclusive coverage parts labor and travel.	RoHS Compliant
	C-Tick Compliant
	GoST-R
	CE Marked
	Certifications
	cUL Listed
	UL Listed
	IEC 61508
	UL 508C
	EN 62061
	EN ISO 13849-1

Product specifications

Max overload

110% for 1 minute

Communication interface

PROFIBUS-DP

Motor control modes

Frequency Control, Speed Control, Open Loop Speed Control,
Open Loop Torque Control

Internal DC choke

Yes

Conformal coated boards

Yes

Low overload (VT) kW

2.2 kW

Low overload (VT) hp

3 HP

Low overload (VT) amps

4.5A

Amperage Rating

4.50A

Communications onboard

BACnet/IP, Modbus TCP, Modbus RTU, BACnet MS/TP

Motor type

Induction

Output frequency range

0 - 400 Hz

Series

DH1

Electromagnetic compatibility filter

EMC

User interface

Graphical Keypad

Relay outputs

3

Power consumption

2.20 kW

Resources

Catalogs

[Adjustable Frequency Drives](#)

Specifications and datasheets

[Eaton Specification Sheet - DH1-354D5FB-C54C](#)

Input voltage range

525 - 600 Vac

Horsepower

3 hp

Recommended fuse size

10A

Keypad

Included

Input frequency range

50 - 60 Hz

Voltage rating

575 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)