

Eaton 5P750

Catalog Number: 5P750

Eaton 5P UPS, Tower, 750 VA, 600 W, 5-15P input, Outputs: (8) 5-15R, 120V, true sine wave, network card optional



General specifications

Product Name

Eaton 5P UPS

Catalog Number

5P750

UPC

743172042989

Product Length/Depth

13.6 in

Product Height

9.1 in

Product Width

5.9 in

Product Weight

23.6 lb

Warranty

3 year on electronics, 3 year on batteries with registration

Compliances

RoHS Compliant

CE Marked

Certifications

UL 1778

UL 497A

cULus Listed

IEC 62040-2 C1-C2 / EN 55024 /

CISPR22 Class B / FCC part 15 Class B



Powering Business Worldwide

Battery

[Runtime graph](#)

[View runtime graph](#)

[Battery type](#)

Sealed, lead-acid

[Battery replacement](#)

User replaceable

[Battery management](#)

ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)

[Extended battery capability](#)

None; See Eaton 5PX UPS for extended runtimes options

Electrical output

[Voltage](#)

120V

[Receptacle](#)

(8) 5-15R

[Wattage](#)

600 W

[Output voltage range](#)

102-132 Vac

[Output frequency](#)

50/60 Hz

[Output nominal voltage](#)

120V default (100/120/125V)

[Topology](#)

Line-interactive

Electrical input

[Input connection](#)

5-15P

[Input nominal voltage](#)

120V default (100/110/120/127V)

[Nominal frequency](#)

50-60 Hz

[Input power factor](#)

0.8

[Input cord length](#)

6 ft

[Input voltage range](#)

89-151 Vac (adjustable to 70-153 Vac)

[Input frequency range](#)

47-70 Hz (50 Hz system), 56.5-70 Hz (60 Hz system), 40-70 Hz in low-sensitivity mode

Communications

[Communication](#)

RS-232 (RJ45) ports; USB port as standard (HID). 6-foot RS-232 and USB cables included

[Expansion slots](#)

One slot; Gigabit Network Card (Network-M2) is optional

[Software compatibility](#)

Eaton Intelligent Power Manager

Environmental

[Altitude](#)

Up to 10,000 ft (3000m) without de-rating

[Noise level](#)

<45 dB at 1 meter

[Temperature range](#)

0° to 35°C (32° to 95°F)

[BTU Rating](#)

Online: 82, Battery 389

[Relative humidity](#)

0-90% non-condensing

Additional specifications

Form factor

Tower

Package contents

5P UPS
User manual CD
Intelligent Power Software
Suite CD
Quick start guide
USB cable
RS-232 serial cable

Color

Black/silver

Efficiency

97%

Warranty and support

Standard factory warranty

3-YEAR FACTORY
WARRANTY w/
REGISTRATION
-3 years
-Parts, electronics, and
batteries coverage
-Standard ground shipping
-Technical support

Extended service plans

ADVANCED DEPOT
EXCHANGE
-5-YEAR DEPOT REPAIR:
5SW5Y-950UC
-Expedited parts coverage
for 5 years
-Parts, electronics and UPS
batteries coverage
-Next business day shipping
-Technical support
5-YEAR ON-SITE PLAN:
WFLN75XX-2509UC
- On-site parts and labor

Resources

Brochures

5-series UPS overview brochure
Eaton 5P Tower UPS brochure

Drawings

Eaton 5P750 3D drawing
Eaton 5P UPS 3D drawings
Eaton 5P UPS visio stencils
Eaton 5P750 tower 2D drawing

Manuals and user guides

Eaton 5P UPS installation and user manual

Specifications and datasheets

Eaton Specification Sheet - 5P750

coverage for years 5

- Parts, electronics and UPS

batteries coverage

- 24x7 on-site labor

coverage, next-day

response

- Next-day shipping

- Technical support



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)