

SLMT6-13W

6" SLIMLED MULTI, up to 1070 Lumens, 13 Watt,
Color Selectable
Recessed Downlighting

Job Information		
Project Name		Type
Location		
Quantity		Date
Contact/Phone		
Notes		

Features

Body

Durable airtight aluminum body with twist-and-lock trim that allows for ease and versatility. White trim included, black and brushed nickel trims sold separately.

LED Characteristics

This general application light fixture features a 13 watt LED module that maintains uniform intensity producing up to 1070 lumens; with a typical CRI of 90. CCT select switch 2700 K (default) - 5000 K color temperature.

Dimming

100%-10% dimming capability. This fixture is compatible with industry standard forward/reverse phase dimmers, TRIAC/ELV dimmers. For compatible dimmers, visit www.liteline.com/SlimLEDMulti

Beam Spread

The fixture lens provides 110° beam spread.

Mounting

Can be mounted to an industry standard

3.5"/4" octagon box (JBox / standard slab box) with minimum depth of 1.5" (40mm) via mounting holes or a compatible 6" recessed housing (retrofit kit sold separately - P-SLMT6-6CAN).

Compatible Recessed Housings

- RF601CAT series
- RF602ICAT series

LED Driver

Built-in on board driver with 120V AC input.

Quick Connect push-in terminals

"Quick connect" push-in terminals for fast and easy wiring.

Operating Temperature

-30°C~45°C (-22°F~113°F)

Environment

- Suitable for wet locations.
- Fire-rated when used in a fire-rated octagon box.
- Indoor/Outdoor rated.



SPECIFICATION	
Application	Recessed / Surface-mount Downlight
Approved Location	Wet
Beam Angle	110°
CCT	2700 K / 3000 K / 3500 K / 4000 K / 5000 K
Certification	cETLus
Color	WH (BK/BN trims sold separately)
CRI	90+
Dimming	Yes
Dimming Tech	Forward/Reverse phase / TRIAC/ELV
Energy Star	Yes
Input	120V, 60Hz
LM79	Yes
LM80	Yes
Lumens	Up to 1070
Lumens per Watt	Up to 83
Power Factor	0.9
Projected Life	70% @ 50,000 hrs
Title 24	Yes
Warranty	5-Year
Wattage	13W

CCT	Lumens
2700 K	960
3000 K	996
3500 K	1040
4000 K	1060
5000 K	1070




Description


The SLMT6-13W is a 13 watt 6" round downlight for retrofit application onto existing 6" recessed housings or 3.5"/4" octagon box. It is a high-performance, easy to install residential grade downlight solution that offers good light output, energy-efficiency and streamlined design. Suitable for wet locations.



Mounting Options



6" CAN*



J-BOX

* Retrofit Kit sold separately (P-SLMT6-6CAN).



Notes: Accessories are sold separately. For additional options please consult your Liteline representative.
Due to our continued efforts to improve our products, product specifications are subject to change without notice.

Ordering Guide



SLMT6-13W

6" SLIMLED MULTI color selectable round downlight, 13W, with white trim.

Accessories



P-SLMT6-6CAN

6" Housing accessories (Retrofit kit)
E26 lampholder + wire + connectors +
spring clips



SLMT6-RT-BK

Optional trim for 6" SlimLED Multi, Black.

SLMT6-RT-BN

Optional trim for 6" SlimLED Multi,
Brushed Nickel.



LC-CRTL-3WAY-1

OnCloud Smart Wi-Fi 3-way switch.
Suitable for 3-way or 4-way switch
applications.



LC-CRTL-DIM-1

OnCloud Smart Wi-Fi dimmer. Features
an ON/OFF press and a 7 level
touch slider.