

# Eaton FAZ-C40/3

Catalog Number: FAZ-C40/3

Eaton FAZ supplementary protector, UL 1077 Industrial miniature circuit breaker - supplementary protector, Medium levels of inrush current are expected, 40 A, 15 kAIC, Three-pole, 5-10X /n, 50-60 Hz, Standard terminals, C Curve



## General specifications

<b>Product Name</b>	Eaton FAZ supplementary protector	<b>Catalog Number</b>	FAZ-C40/3
<b>EAN</b>	4015082788773	<b>Product Length/Depth</b>	2.07 in
<b>Product Height</b>	2.07 in	<b>Product Width</b>	2 in
<b>Product Weight</b>	0.8 lb	<b>Warranty</b>	1 year
<b>Certifications</b>	CSA Std. C22.2 No.235 IEC 60947-2 UL 1077	<b>Catalog Notes</b>	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

## Physical Attributes

### Number of poles

Three-pole

### Terminals

Standard

### Type

UL 1077 Industrial miniature circuit breaker - supplementary protector

## Performance Ratings

### Amperage Rating

40 A

### Circuit protection

C curve

### Frequency rating

50-60 Hz

### Interrupt rating

15 kAIC

### Trip Type

5-10X /n

## Miscellaneous

### Application

Suitable for applications where medium levels of inrush current are expected

## Resources

### Brochures

[Industrial miniature circuit breakers UL 489](#)

### Catalogs

[Eaton's Volume 4—Circuit Protection](#)

### Specifications and datasheets

[Eaton Specification Sheet - FAZ-C40/3](#)

[Product Data Sheet - FAZ-C40/3](#)



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)