

Eaton SPD120600D3J

Catalog Number: SPD120600D3J

Surge Protection Device, SPD series, For motor control centers, 120 kAIC, 600V delta (4W+G), Standard feature package and surge counter, Internal integrated mount, 840 L-G, 840 L-L operating voltage

General specifications



Product Name	Catalog Number
Eaton SPD series surge protection device	SPD120600D3J
	UPC
	786685325002
Product Length/Depth	Product Height
9.5 in	3.45 in
Product Width	Product Weight
5.4 in	3.5 lb
Warranty	Certifications
15 year	UL 1449
	UL Listed

defaultTaxonomyAttributeLabel

Type

SPD

Special features

Meets or exceeds the requirements specified in IBC @2006, CBC2007, and UBC@Zone 4. Audible alarm with silence button. Form C relay contact. EMI/RFI filtering, providing up to 50 dB of noise attenuation from 10 kHz to 100 MHz. Surge counter with rest button

Accessories

Standard feature package and surge counter

Frequency rating

50/60 Hz

Interrupt rating

200 kAIC

Nominal Discharge Current

20 kA

Operating voltage

840 L-G, 840 L-L

Used with

Motor control centers

Voltage rating

600 delta (4W+G)

Surge current

120 kA per phase

Short-circuit rating

200 kA

Operating temperature

-40 to 50 °C

Mounting Method

Internal integrated

Resources

Brochures

[Eaton's SPD Series \(Integrated Versions\) Product Aid](#)

Catalogs

[Eaton's Volume 3—Power Distribution and Control Assemblies](#)

Installation instructions

[Eaton SPD Series - Surge Protective Device For Integrated Units](#)

Specifications and datasheets

[Eaton's SPD Series \(Integrated Versions\) Data Sheet](#)

[Eaton Specification Sheet - SPD120600D3J](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)