


Transformer Specifications	
PRIMARY VOLTAGE(S)	208/277
SECONDARY VOLTAGE(S)	120
RATED V.A.	100
RATED FREQUENCY	50/60
INSULATION CLASS	105
AGENCY APPROVALS	UL, CUL
ESTIMATED WEIGHT	4.5 LBS

TEST REQUIREMENTS	
H3-H2-H1	X2-X1
DC VOLT(S)	207.9-277
DC VOLT(S)	208-277
F.L. AMPS	0.619
HI-POT	3000V
EXCITING AMPS	0.29AMPS @ 277 VOLT.S, 50HZ
EXCITING WATTS	8.2 MAX



NOTE:
1. ALL MEASUREMENTS IN INCHES (MM)

Culter-Hammer INDUSTRIAL CONTROL TRANSFORMER
 100VA 50/60Hz
 TEMP CL. 105°C
 CAT. NO. C0100E3AFB
 SERIES 2
 B100-2226-B
 UL US LISTED 792X

UNLESS OTHERWISE SPECIFIED	
DIMENSIONS IN INCHES	DATE 07/01/09
ONE PLACE DEC	DRP/TER/DESIGNER S. CASTRO
TWO PLACE DEC	DATE 07/01/09
THREE PLACE DEC	APPD ERROBLES
ANGLE PER DEC	DATE 07/01/09
VOLTAJE	APPD O.SANDOVAL
AMPERAGE	ENG. REF. 07/01/09
FORCE/TORQUE/SPEED	TEMPERATURE
±10%	±131.45°F
DIMENSIONS TO BE INTERPRETED IN ACCORDANCE WITH ASME Y14.5M-1994	TOOL REF
EXCEED SERIAL DIMENSIONS PER SERIAL SPEC. 20	DSPEC
PRODUCTION	SCALE B
	SCALE C0100E3AFB.DWG
	PARTS LIST
	DWG NO C0100E3AFB
	PRODUCT CODE
	SHEET NO 1 OF 1

REVISION DT ---
 EAU J0240 FRM1 REV 05/05/08
 4 3 2
 © 2008 Eaton Corporation. All Rights Reserved

