Eaton 1563PMURF

Catalog Number: 1563PMURF

Eaton LV Unipak capacitor bank, UNIPAK, Low Voltage Fixed Capacitor Banks, 14.7A, 600V, Three-phase, 15 kVAR, Protected, Neon red blown-fuse indicating lights, Three slottedblade-type fuses, A2 Frame

General specifications

Product Name Eaton LV Unipak capacitor bank

UPC 782116059096

Product Height 22.3 in

Product Weight 29.38 lb

Certifications

CSA Certified

UL Listed

1563PMURF Product Length/Depth 5.954 in

Catalog Number

Product Width 8.5 in

Warranty

Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Catalog Notes

Multiply the 240V kVAR rating by 0.75 to calculate the kVAR value at 208V.





defaultTaxonomyAttributeLabel

Туре

UNIPAK

Amperage Rating

14.70A

Fuse type

Three slottedblade type fuses with 200,000 ampere interrupting capacity, Fuses mounted on stand-off bushings or fuse blocks, solderless connectors for easy hookup of incoming line conductors.

Phase

Three-phase

Product Category Low Voltage Fixed Capacitor Banks

Voltage rating 600 V

Enclosure NEMA 1, NEMA 3R

Enclosure material

14 gauge steel finished with durable powder coat finish

Frame size

A2

Indicators

Red, neon blown-fuse indicating lights are protected by transparent weatherproof guard

Protection Three fuses, three lights

Rating

15 kVAR

Resources

Catalogs

Eaton's Volume 3—Power Distribution and Control Assemblies

Specifications and datasheets

Eaton Specification Sheet - 1563PMURF



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com © 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

Eaton.comAll other trademarks are© 2024 Eaton. All Rightsproperty of their respectiveReserved.owners.



Eaton.com/socialmedia